



 **ORBLOX**



THE NEW RETRACTABLE TYPE FALL ARRESTER FROM FALL SAFE®
SMALLER • LIGHTER • STRONGER
TESTED TO LATEST AND SAFER EN 360:2023 STANDARD



20mm FS Twist Lock Karabiner

In lightweight aluminium - attach to user - optional FS919 bracket.

Anti Rotating Attachment

Durable Storage Pouch

Double Wing Energy Absorber

More compact and lightweight with increased performance.

Rotatable Swivel

Ultralight Durable Nylon Casing

Fall Indicator

CE Label With QRCode | RFID



Compatible with FS INSPECTOR®

FSS30E
FALL ARREST BLOCKS- SHARP
EDGE 2.30M

60mm FS Large Hook

Double action locking in lightweight aluminium attach to structure.

Webbing Abrasion Protector



CE EN 360:2023



TECHNICAL INFORMATION

REF No.	FS930E
LIFESPAN	10 Years
MIN/ MAX RATED LOAD	50 Kg - 140 Kg
INSPECTION	Yearly
TRACEABILITY	S/N, QR Code
STANDARD	EN 360:2023
TESTED APPLICATIONS	Overhead, Foot Level Horizontal, Foot Level Vertical
TEMPERATURE	-30°C, +50°C, 85% HR
ENVIRONMENT	Heat, Cold, Wet, Corrosion
STATIC STRENGTH	>15 kN
BRAKING FORCE	<6 KN
MINIMUM CLEARANCE - MC (BELOW USER FEET)	2.0m Vertical Overhead 3.5m Vertical Foot FF2 4.0m Horizontal Foot Offset
RETRACTION TENSION	~40N

SPECIFICATIONS

MATERIAL	Steel, Carbon, UHMWPE®, Aluminium, PA66, Iron
WEBBING TYPE	23MM, UHMWPE Hi Performace Fiber
FALL ARREST INDICATOR	Yes
CONNECTORS	Aluminium
ENERGY ABSORBER	Yes
SHARP EDGE TESTED (RADIUS 0.5MM STEEL BAR)	Yes
MAX USERS NO.	1
HOUSING	PA66 + Glass filled
CHASSIS	Stainless steel, carbon steel
LENGTH	2.3M
WEIGHT (INCL. CONNECTORS)	1.3Kg



Scan

for more information

IMPORTANT!

- Do Not Use 2X FS930E in twin mode, for this application use FS930E-TWIN RTFA
- Always read and understand the user instructions before use.

FS
FALL SAFE®

SureWerx®