



FS803

FILUM - ANCHOR WIRE

The FALL SAFE® FS803 consists of an 8mm galvanized steel cable, whose ends are joined by a carabiner. Works as a temporary and portable fall arrest system.



TECHNICAL INFORMATION

LIFESPAN	UNDEFINED
MAXIMUM LOAD	CE - 12KN
INSPECTION	Yearly
TRACEABILITY	S/N QR Code
STANDARDS	CE - EN795:2012-B
INTRASTAT	63079098

PRODUCT PHOTOS



SPECIFICATIONS

MATERIAL	Galvanized steel cable and aluminium
CLASS	B
MAX STRENGTH	12kN
MAX USERS NO.	1
DIMENSIONS	0.50 m to 4 m
WEIGHT PER SIZE EAN/UPC PER SIZE	FS803-0.5M - 0.25kg - 5605423420289 FS803-4M - 2.80kg - 5605423420234 FS803-3M - 2.60kg - 5605423420241 FS803-2M-50004 - 2.00kg - 5605423807288 FS803-2M - 2.00kg - 5605423420258 FS803-2.4M - 2.30kg - 5605423801552 FS803-1M - 0.60kg - 5605423420401 FS803-1.5M - 0.75kg - 5605423420272



FS803

FILUM - ANCHOR WIRE

Le système FALL SAFE® FS803 est composé d'un câble en acier galvanisé de 8 mm de diamètre, dont les extrémités sont reliées par un mousqueton. Il fonctionne comme un système antichute portable et temporaire.



INFORMATIONS TECHNIQUES

DURÉE DE VIE	UNDEFINED
CHARGE MAXIMALE	CE - 12KN
INSPECTION	Yearly
TRAÇABILITÉ	S/N QR Code
NORMES	CE - EN795:2012-B
INTRASTAT	63079098

PHOTOS PRODUIT



SPÉCIFICATIONS

MATÉRIAU	Câble en acier galvanisé et en aluminium
CLASSE	B
RÉSISTANCE MAXIMALE	12kN
NOMBRE MAXIMAL D'UTILISATEURS	1
DIMENSIONS	0.50 m to 4 m
WEIGHT PER SIZE EAN/UPC PER SIZE	FS803-0.5M - 0.25kg - 5605423420289 FS803-4M - 2.80kg - 5605423420234 FS803-3M - 2.60kg - 5605423420241 FS803-2M-50004 - 2.00kg - 5605423807288 FS803-2M - 2.00kg - 5605423420258 FS803-2.4M - 2.30kg - 5605423801552 FS803-1M - 0.60kg - 5605423420401 FS803-1.5M - 0.75kg - 5605423420272



FS803

FILUM - ANCHOR WIRE

El FALL SAFE® FS803 consta de un cable de acero galvanizado de 8 mm, cuyos extremos están unidos por un mosquetón. Funciona como un sistema portátil y temporal de detención de caídas.



TECHNICAL INFORMATION

LIFESPAN	UNDEFINED
MAXIMUM LOAD	CE - 12KN
INSPECTION	Yearly
TRACEABILITY	S/N QR Code
STANDARDS	CE - EN795:2012-B
INTRASTAT	63079098

PRODUCT PHOTOS



SPECIFICATIONS

MATERIAL	Cable de acero galvanizado y aluminio
CLASS	B
MAX STRENGTH	12kN
MAX USERS NO.	1
DIMENSIONS	0.50 m to 4 m
WEIGHT PER SIZE EAN/UPC PER SIZE	FS803-0.5M - 0.25kg - 5605423420289 FS803-4M - 2.80kg - 5605423420234 FS803-3M - 2.60kg - 5605423420241 FS803-2M-50004 - 2.00kg - 5605423807288 FS803-2M - 2.00kg - 5605423420258 FS803-2.4M - 2.30kg - 5605423801552 FS803-1M - 0.60kg - 5605423420401 FS803-1.5M - 0.75kg - 5605423420272



FS803

FILUM - ANCHOR WIRE

O FALL SAFE® FS803 é constituído por um cabo de aço galvanizado de 8mm, em que as suas extremidades são unidas por um mosquetão. Funciona como sistema ant queda temporário e portátil.



Informação Técnica

TEMPO DE VIDA ÚTIL	UNDEFINED
CARGA MÁXIMA	CE - 12KN
INSPEÇÃO	Yearly
RASTREABILIDADE	S/N QR Code
NORMAS	CE - EN795:2012-B
INTRASTAT	63079098

Imagens do Produto



ESPECIFICAÇÕES

MATERIAL	Cabo de aço galvanizado e alumínio
CLASSE	B
FORÇA MÁX	12kN
Nº MÁX UTILIZADORES	1
DIMENSÕES	0.50 m to 4 m
WEIGHT PER SIZE EAN/UPC PER SIZE	FS803-0.5M - 0.25kg - 5605423420289
	FS803-4M - 2.80kg - 5605423420234
	FS803-3M - 2.60kg - 5605423420241
	FS803-2M-50004 - 2.00kg - 5605423807288
	FS803-2M - 2.00kg - 5605423420258
	FS803-2.4M - 2.30kg - 5605423801552
	FS803-1M - 0.60kg - 5605423420401
	FS803-1.5M - 0.75kg - 5605423420272