



BASIC

FS516-LN

CHIMANGO 2 - Y LANYARD WITH ENERGY ABSORBER

FS516 CHIMANGO 2 is a double lanyard that physically links the user to the workplace structure and arrests the free fall of the user (EN354, EN355) . It is made with 27mm polyester webbing, a PES 45mm energy absorber, PES heavy duty seams, and support maximum load of 140 kg.



TECHNICAL INFORMATION

LIFESPAN	10
MAXIMUM LOAD	CE - 140kg
INSPECTION	N/A
TRACEABILITY	N/A S/N QR Code
STANDARDS	CE - EN354:2011 CE - EN355:2003
INTRASTAT	56090000

PRODUCT PHOTOS



SPECIFICATIONS

MATERIAL	PES, Polimero, Steel, Silicone
WEBBING TYPE	PES webbing 27 mm x 3 mm
ROPE TYPE	PES webbing 27mm
CONNECTORS	FS802 screw lock 25kN; FS843 auto lock 25kN (other combinations on request)
MAX LENGTH	2m
ENERGY ABSORBER	Yes
SEAMS PROTECTOR	No
SHARP EDGE TESTED	No
WEIGHT PER SIZE EAN/UPC PER SIZE	FS516-LN-1M - 1,06kg - 5605423700855 FS516-LN-1.5M - 1,59kg - 5605423700763 FS516-LN-2M - 2,12kg - 5605423700961



BASIC

FS516-LN

CHIMANGO 2 - Y LANYARD WITH ENERGY ABSORBER

FS516 CHIMANGO 2 is a double lanyard that physically links the user to the workplace structure and arrests the free fall of the user (EN354, EN355) . It is made with 27mm polyester webbing, a PES 45mm energy absorber, PES heavy duty seams, and support maximum load of 140 kg.



INFORMATIONS TECHNIQUES

DURÉE DE VIE	10
CHARGE MAXIMALE	CE - 140kg
INSPECTION	N/A
TRAÇABILITÉ	N/A S/N QR Code
NORMES	CE - EN354:2011 CE - EN355:2003
INTRASTAT	56090000

PHOTOS PRODUIT



SPÉCIFICATIONS

WEIGHT PER SIZE EAN/UPC PER SIZE

FS516-LN-1M - 1,06kg - 5605423700855
FS516-LN-1.5M - 1,59kg - 5605423700763
FS516-LN-2M - 2,12kg - 5605423700961



BASIC

FS516-LN

CHIMANGO 2 - Y LANYARD WITH ENERGY ABSORBER

FS516 CHIMANGO 2 é uma longe dupla que liga fisicamente o utilizador à estrutura do local de trabalho e impede a queda livre do utilizador (EN354, EN355) . É feito com fita de poliéster de 27 mm, absorvedor de energia PES de 45 mm, costuras de poliéster e suporta carga máxima de 140 kg.



Informação Técnica

TEMPO DE VIDA ÚTIL	10
CARGA MÁXIMA	CE - 140kg
INSPEÇÃO	N/A
RASTREABILIDADE	N/A S/N QR Code
NORMAS	CE - EN354:2011 CE - EN355:2003
INTRASTAT	56090000

Imagens do Produto



ESPECIFICAÇÕES

MATERIAL	PES, Polímero, Aço, Silicone
TIPO DE FITA	Fita PES 27 mm x 3 mm
TIPO DE CORDA	Fita PES 27mm
CONECTORES	FS802 screw lock 25kN; FS843 auto lock 25kN (outras combinações a pedido)
COMPRIMENTO MÁX	2m
ABSORBEDOR DE ENERGIA	Sim
PROTETOR DE COSTURAS	Não
TESTADO ARESTAS CORTANTES	Não
WEIGHT PER SIZE EAN/UPC PER SIZE	FS516-LN-1M - 1,06kg - 5605423700855 FS516-LN-1.5M - 1,59kg - 5605423700763 FS516-LN-2M - 2,12kg - 5605423700961