



FS907

EVAK - RESCUE EQUIPMENT

The FS907 is the ideal evacuation kit. Includes a controlled descent device, with integrated lifting and reverse locking. It is the ideal device for rescuing victims or yourself. During the descent process, the centrifugal brake maintains the device at a constant speed throughout the descent. With the help of the new deviation point on the device, the descent speed can be regulated. This device also ensures that, during a rescue, the victim only moves in an upward direction, therefore there is no danger of the victim falling. The kit also consists of an anchor strap and a telescopic pole, as well as a transport case.



The information contained in this video is not sufficient to guarantee the proper use of the equipment. It must be used by a person with technical and practical knowledge of its correct use and it requires a careful reading of the instructions available at www.fallsafe-online.com. FS® may modify or update technical information at any time.



TECHNICAL INFORMATION

LIFESPAN	N/A
MAXIMUM LOAD	CE - 200kg
INSPECTION	Yearly
TRACEABILITY	S/N QR Code
STANDARDS	CE - N/A
INTRASTAT	63079098

PRODUCT PHOTOS



SPECIFICATIONS

ROPE TYPE	Kernmantle rope Ø 10.5 mm
DEVICE	Resistant and low-maintenance descent device with swivel with ball bearing
CONNECTORS	1x steel screw lock + 2x hooks
MAX LENGTH	200 m
MAX RATED LOAD	140kg
MAX USERS NO.	1
HOUSING	Aluminium
LENGTH	Multiple lengths available

WEIGHT PER SIZE EAN/UPC PER SIZE	FS907-20M - 6,42kg - 5605423430301
	FS907-10M - 0,00kg -
	FS907J-20M - 2,60kg - 5605423810387
	FS907-90M - 9,90kg - 5605423430677
	FS907-80M - 7,20kg - 5605423430554
	FS907-70M - 6,70kg - 5605423813685
	FS907-60M - 6,30kg - 5605423752328
	FS907-50M - 5,40kg - 5605423751284
	FS907-40M - 4,40kg - 5605423752311
	FS907-30M - 3,30kg - 5605423430608
	FS907-200M - 25,50kg - 5605423802993
	FS907-150M - 13,50kg - 5605423802948
FS907-100M - 12,70kg - 5605423435283	



FS907

EVAK - RESCUE EQUIPMENT

The FS907 is the ideal evacuation kit. Includes a controlled descent device, with integrated lifting and reverse locking. It is the ideal device for rescuing victims or yourself. During the descent process, the centrifugal brake maintains the device at a constant speed throughout the descent. With the help of the new deviation point on the device, the descent speed can be regulated. This device also ensures that, during a rescue, the victim only moves in an upward direction, therefore there is no danger of the victim falling. The kit also consists of an anchor strap and a telescopic pole, as well as a transport case.



The information contained in this video is not sufficient to guarantee the proper use of the equipment. It must be used by a person with technical and practical knowledge of its correct use and it requires a careful reading of the instructions available at www.fallsafe-online.com. FS® may modify or update technical information at any time.



INFORMATIONS TECHNIQUES

DURÉE DE VIE	N/A
CHARGE MAXIMALE	CE - 200kg
INSPECTION	Yearly
TRAÇABILITÉ	S/N QR Code
NORMES	CE - N/A
INTRASTAT	63079098

PHOTOS PRODUIT



SPÉCIFICATIONS

WEIGHT PER SIZE EAN/UPC PER SIZE

- FS907-20M - 6,42kg - 5605423430301
- FS907-10M - 0,00kg -
- FS907J-20M - 2,60kg - 5605423810387
- FS907-90M - 9,90kg - 5605423430677
- FS907-80M - 7,20kg - 5605423430554
- FS907-70M - 6,70kg - 5605423813685
- FS907-60M - 6,30kg - 5605423752328
- FS907-50M - 5,40kg - 5605423751284
- FS907-40M - 4,40kg - 5605423752311
- FS907-30M - 3,30kg - 5605423430608
- FS907-200M - 25,50kg - 5605423802993
- FS907-150M - 13,50kg - 5605423802948
- FS907-100M - 12,70kg - 5605423435283



FS907

EVAK - RESCUE EQUIPMENT

The FS907 is the ideal evacuation kit. Includes a controlled descent device, with integrated lifting and reverse locking. It is the ideal device for rescuing victims or yourself. During the descent process, the centrifugal brake maintains the device at a constant speed throughout the descent. With the help of the new deviation point on the device, the descent speed can be regulated. This device also ensures that, during a rescue, the victim only moves in an upward direction, therefore there is no danger of the victim falling. The kit also consists of an anchor strap and a telescopic pole, as well as a transport case.



The information contained in this video is not sufficient to guarantee the proper use of the equipment. It must be used by a person with technical and practical knowledge of its correct use and it requires a careful reading of the instructions available at www.fallsafe-online.com. FS® may modify or update technical information at any time.



TECHNICAL INFORMATION

LIFESPAN	N/A
MAXIMUM LOAD	CE - 200kg
INSPECTION	Yearly
TRACEABILITY	S/N QR Code
STANDARDS	CE - N/A
INTRASTAT	63079098

PRODUCT PHOTOS



SPECIFICATIONS

WEIGHT PER SIZE EAN/UPC PER SIZE

- FS907-20M - 6,42kg - 5605423430301
- FS907-10M - 0,00kg -
- FS907J-20M - 2,60kg - 5605423810387
- FS907-90M - 9,90kg - 5605423430677
- FS907-80M - 7,20kg - 5605423430554
- FS907-70M - 6,70kg - 5605423813685
- FS907-60M - 6,30kg - 5605423752328
- FS907-50M - 5,40kg - 5605423751284
- FS907-40M - 4,40kg - 5605423752311
- FS907-30M - 3,30kg - 5605423430608
- FS907-200M - 25,50kg - 5605423802993
- FS907-150M - 13,50kg - 5605423802948
- FS907-100M - 12,70kg - 5605423435283



FS907

EVAK - RESCUE EQUIPMENT

O FS907 é um kit ideal para evacuação.

Inclui um dispositivo de descida controlada, com recurso a elevação integrado e bloqueio reverso. É o dispositivo ideal para o resgate de vítimas ou do próprio.

Durante o processo de descida, o travão centrífugo mantém o dispositivo a uma velocidade constante durante toda a descida. Com a ajuda do novo ponto de desvio no dispositivo, a velocidade de descida pode ser regulada.

Este dispositivo garante ainda que, durante um resgate, a vítima só se desloque na direção ascendente, portanto não há perigo de queda da vítima.

O kit é ainda composto por uma cinta de ancoragem e uma vara telescópica, assim como uma mala de transporte.



The information contained in this video is not sufficient to guarantee the proper use of the equipment. It must be used by a person with technical and practical knowledge of its correct use and it requires a careful reading of the instructions available at www.fallsafe-online.com. FS® may modify or update technical information at any time.



Informação Técnica

TEMPO DE VIDA ÚTIL	N/A
CARGA MÁXIMA	CE - 200kg
INSPEÇÃO	Yearly
RASTREABILIDADE	S/N QR Code
NORMAS	CE - N/A
INTRASTAT	63079098

Imagens do Produto



ESPECIFICAÇÕES

TIPO DE CORDA	Corda Kernmantle Ø 10.5 mm
DISPOSITIVO	Dispositivo de descida resistente e de baixa manutenção
CONECTORES	1x conector aço + 2x ganchos
COMPRIMENTO MÁX	200 m
CARGA MÁXIMA	140kg
Nº MÁX UTILIZADORES	1
INVÓLUCRO	Alumínio
COMPRIMENTO	Vários comprimentos disponíveis
WEIGHT PER SIZE EAN/UPC PER SIZE	FS907-20M - 6,42kg - 5605423430301 FS907-10M - 0,00kg - FS907J-20M - 2,60kg - 5605423810387 FS907-90M - 9,90kg - 5605423430677 FS907-80M - 7,20kg - 5605423430554 FS907-70M - 6,70kg - 5605423813685 FS907-60M - 6,30kg - 5605423752328 FS907-50M - 5,40kg - 5605423751284 FS907-40M - 4,40kg - 5605423752311 FS907-30M - 3,30kg - 5605423430608 FS907-200M - 25,50kg - 5605423802993 FS907-150M - 13,50kg - 5605423802948 FS907-100M - 12,70kg - 5605423435283