



**PROFESSIONAL**

**FS511-CB**

**STERTX EVO - SINGLE LANYARD WITH ENERGY ABSORBER - EUROPEAN VERSION**

FS511 - STERTX EVO is a single lanyard (EN354, EN355) that physically links the user to the workplace structure and arrests the free fall in case of it. This lanyard is made with 27mm polyester webbing, a PES 45mm energy absorber and PES heavy duty seams. It supports a maximum load of 140 kg. The lime colored seams contrast with the black webbing making it easier to inspect the seams during periodic inspection. The design of this equipment, with the retractable webbing, at rest, makes the webbing shorter and does not get in the way of the user.

**TECHNICAL INFORMATION**

LIFESPAN	10
MAXIMUM LOAD	CE - 140kg
INSPECTION	Yearly
TRACEABILITY	S/N QR Code
STANDARDS	CE - EN354:2010 CE - EN355:2002
INTRASTAT	56090000

**PRODUCT PHOTOS**



**SPECIFICATIONS**

MATERIAL	PES, ALU, Silicone
WEBBING TYPE	PES retractable tubular webbing 27mm
CONNECTORS	FS33562 ALU auto lock 25kN; FS821 ALU auto lock 23kN (other combinations on request)
MAX LENGTH	1.80 m
ENERGY ABSORBER	Yes, PES - up to 140 Kg
SEAMS PROTECTOR	No
SHARP EDGE TESTED	No
WEIGHT PER SIZE   EAN PER SIZE	FS511-CB-1.8M - 1,10kg - 5605423808971



**PROFESSIONAL**

**FS511-CB**

**STERTX EVO - SINGLE LANYARD WITH ENERGY ABSORBER - EUROPEAN VERSION**

FS511 - STERTX EVO é uma longe simples (EN354, EN355) que liga fisicamente o utilizador à estrutura do local de trabalho e impede a queda livre em caso de queda. Esta longe é feita com tecido de poliéster de 27 mm, um absorvedor de energia PES de 45 mm e costuras pesadas de PES. Suporta uma carga máxima de 140 kg. As costuras cor lima contrastam com a fita preta, facilitando a inspeção das costuras durante a inspeção periódica. O design deste equipamento, com a fita retrátil, em repouso, torna a fita mais curta e não atrapalha o utilizador.

**Informação Técnica**

TEMPO DE VIDA ÚTIL	10
CARGA MÁXIMA	CE - 140kg
INSPEÇÃO	Yearly
RASTREABILIDADE	S/N QR Code
NORMAS	CE - EN354:2010 CE - EN355:2002
INTRASTAT	56090000

**Imagens do Produto**



**ESPECIFICAÇÕES**

MATERIAL	PES, ALU, Silicone
TIPO DE FITA	PES retractable tubular webbing 27mm
CONECTORES	FS33562 ALU auto lock 25kN; FS821 ALU auto lock 23kN (other combinations on request)
COMPRIMENTO MÁX	1.80 m
ABSORBEDOR DE ENERGIA	Yes, PES - up to 140 Kg
PROTETOR DE COSTURAS	No
TESTADO ARESTAS CORTANTES	No
PESO POR TAMANHO   EAN POR TAMANHO	FS511-CB-1.8M - 1,10kg - 5605423808971