

FS883

TOGGLE ANCHOR

FALL SAFE® FS883 is a versatile, portable steel anchor used exclusively for fall protection. The toggle lock can be placed on horizontal, vertical and overhead/ceiling surfaces. It has a 20mm expander screw.
• Minimum Breaking Strength: 22.2 kN
• For hollow core concrete and steel applications
• Multi-directional use

TECHNICAL INFORMATION

LIFESPAN	UNDEFINED
MAXIMUM LOAD	CE - N/A OSHA - N/A ANSI - N/A
INSPECTION	Yearly
TRACEABILITY	S/N
STANDARDS	CE - EN795:2012-B OSHA - OSHA 1910 & 1926 ANSI - ANSI Z359.18-2017
INTRASTAT	73269098

FALL SAFE ON LINE LDA
ZONA INDUSTRIAL DA VARZIELA, RUA B, LOTE 54, 4480-620 VILA DO CONDE
SUPPORT@FALLSAFE-ONLINE.COM | WWW.FALLSAFE-ONLINE.COM

PRODUCT PHOTOS



SPECIFICATIONS

MATERIAL	Steel alloy
MAX STRENGTH	22.2 kN (Maximum break strength)
DIMENSIONS	Connection 38mm; Length 279mm; Mounting Hole 19mm
WEIGHT PER SIZE EAN/UPC PER SIZE	FS883 - 231,00kg -

FALL SAFE ON LINE LDA
ZONA INDUSTRIAL DA VARZIELA, RUA B, LOTE 54, 4480-620 VILA DO CONDE
SUPPORT@FALLSAFE-ONLINE.COM | WWW.FALLSAFE-ONLINE.COM



FS883

TOGGLE ANCHOR

FALL SAFE® FS883 é uma ancoragem versátil, portátil de aço, usada exclusivamente para proteção contra quedas. Pode ser colocada em superfícies horizontais, verticais e superiores/teto. Possui um parafuso expansor de 20mm.

- Resistência mínima à ruptura: 22.2 kN
- Para aplicações em concreto e aço
- Uso multidirecional

Informação Técnica

TEMPO DE VIDA ÚTIL	UNDEFINED
CARGA MÁXIMA	CE - N/A OSHA - N/A ANSI - N/A
INSPEÇÃO	Yearly
RASTREABILIDADE	S/N
NORMAS	CE - EN795:2012-B OSHA - OSHA 1910 & 1926 ANSI - ANSI Z359.18-2017
INTRASTAT	73269098

FALL SAFE ON LINE LDA
ZONA INDUSTRIAL DA VARZIELA, RUA B, LOTE 54, 4480-620 VILA DO CONDE
SUPPORT@FALLSAFE-ONLINE.COM | WWW.FALLSAFE-ONLINE.COM

Imagens do Produto



ESPECIFICAÇÕES

MATERIAL	Cabo de aço
FORÇA MÁX	22.2 kN (Maximum break strength)
DIMENSÕES	Conexão 38mm; Comprimento 279mm
WEIGHT PER SIZE EAN/UPC PER SIZE	FS883 - 231,00kg -

FALL SAFE ON LINE LDA
ZONA INDUSTRIAL DA VARZIELA, RUA B, LOTE 54, 4480-620 VILA DO CONDE
SUPPORT@FALLSAFE-ONLINE.COM | WWW.FALLSAFE-ONLINE.COM