

PROFESSIONAL

FS241.01

SLIM FIRE BRIGADE BELT



FS241.01 is a compact and lightweight belt for use in work positioning (EN358), as well as suspension (EN12277) when associated with the legs FS241.02. It has high visibility polyester webbing with seven reflective filaments for use in low light conditions, black polyester webbing with waterproof treatment, polyester seams that support loads greater than 15kN, comfortable backrest with breathable material, lacquered steel side buckles and special quick-release buckle with central aluminum D-ring.

TECHNICAL INFORMATION

LIFESPAN	10
MAXIMUM LOAD	CE - 140kg
INSPECTION	Yearly
TRACEABILITY	S/N QR Code
STANDARDS	CE - EN358:2018
INTRASTAT	63079098

PRODUCT PHOTOS



SPECIFICATIONS

METAL PARTS	Aluminium, steel
TEXTILE PARTS	Polyester
OTHER COMPONENTS MATERIAL	Plastic and Velcro® (webbing keeper)
WEBBING TYPE	PES webbing 45mm high visibility with reflective strips
D-RINGS	Special ALU d-ring buckle, loops at side
ANCHOR POINTS (A)	3
LUMBAR PADDING	Yes
LEG PADDING	No
SEAT CONNECTION POINT	No
TOOL HOLDERS	2
ADJUSTMENT POINTS	1 (belt) + 3 (legs)
BUCKLES	1 ALU quick connect buckle (belt) + 2 ST bar buckles
FALL ARREST INDICATORS	No
WEIGHT PER SIZE EAN PER SIZE	FS241.01 - 0.80kg - 5605423807134 FS241.02 - 0.20kg - 5605423807141

PROFESSIONAL

FS241.01

SLIM FIRE BRIGADE BELT



FS241.01 é um cinto compacto e leve para usar para posicionamento de trabalho (EN358), bem como suspensão (EN12277) quando associado às pernas FS241.02. Possui fitas de poliéster de alta visibilidade com sete filamentos refletivos para uso em condições de pouca luz, fitas de poliéster pretas com tratamento impermeável, costuras de poliéster que suportam cargas superiores a 15kN, encosto confortável com material respirável, fivelas laterais de aço laqueado e fivela especial de liberação rápida com D-ring central de alumínio.

Informação Técnica

TEMPO DE VIDA ÚTIL	10
CARGA MÁXIMA	CE - 140kg
INSPEÇÃO	Yearly
RASTREABILIDADE	S/N QR Code
NORMAS	CE - EN358:2018
INTRASTAT	63079098

Imagens do Produto



ESPECIFICAÇÕES

COMPONENTES METÁLICOS	Aluminium, steel
COMPONENTES TÊXTEIS	Polyester
OUTROS MATERIAIS	Plastic and Velcro® (webbing keeper)
TIPO DE FITA	PES webbing 45mm high visibility with reflective strips
D-RINGS	Special ALU d-ring buckle, loops at side
PONTOS DE ANCORAGEM (A)	3
PADDING LOMBAR	Yes
PADDING PERNA	No
PONTO LIGAÇÃO DE CADEIRA	No
SUPORTE DE FERRAMENTAS	2
PONTOS DE AJUSTE	1 (belt) + 3 (legs)
FIVELAS	1 ALU quick connect buckle (belt) + 2 ST bar buckles
INDICADORES DE QUEDA	No
PESO POR TAMANHO EAN POR TAMANHO	FS241.01 - 0.80kg - 5605423807134 FS241.02 - 0.20kg - 5605423807141