

PROFESSIONAL

FS242IBD

HARN FLEX BASIC 2D S/M



FS242IBD – HARN FLEX BASIC 2D is a full-body harness designed to provide maximum safety, comfort, and practicality for working at heights. Part of the BASIC PRO line, this model stands out for its versatility and robustness, maintaining the high standard of quality and protection required by professionals operating in vertical environments.

Its main distinguishing feature compared to the FS242IB model is the presence of two metallic D-ring anchorage points: one located on the back (dorsal point A) and another on the chest, offering more connection options for fall arrest systems and ensuring greater operational flexibility depending on the task.

The design is simple yet efficient, with chest adjustment via the IZY Quick Connect buckle, providing quick donning and doffing. The silicone side panels increase comfort and protect the stitching from wear.

It also features spring-type adjustment buckles that allow fast and secure fitting, along with four side rings for carrying tools or accessories, making it easier to access equipment during operation. It includes two positioning points for lateral work, expanding its usability in different scenarios.

The identification system with label, serial number, and QR Code ensures traceability and facilitates PPE management, contributing to compliance with safety regulations.

Ideal for professionals seeking a comprehensive harness with two metallic anchorage points (dorsal and chest), the FS242IBD – HARN FLEX BASIC 2D offers the perfect combination of safety, functionality, and comfort for working at height.



TECHNICAL INFORMATION

LIFESPAN	10 Years
MAXIMUM LOAD	ANSI - 310lbs CSA - 310lbs OSHA - 310lbs
INSPECTION	Yearly
TRACEABILITY	S/N RFID QR Code
STANDARDS	ANSI - Z359.11-2021 CSA - Z259.10-18 OSHA - OSHA 1926.502 OSHA - OSHA 1910.140
INTRASTAT	63079098

PRODUCT PHOTOS



SPECIFICATIONS

METAL PARTS	ALUMINUM AND STEEL ALLOY
TEXTILE PARTS	POLYESTER (PES)
MATERIAL	POLYESTER (PES)
OTHER COMPONENTS MATERIAL	EVA, SILICONE, PA, PEHD AND PES
WEBBING TYPE	POLYESTER (PES)
D-RINGS	2
ANCHOR POINTS (A)	2
TOOL HOLDERS	4
TOOL HOLDERS MAX LOAD	11 lbs
ADJUSTMENT POINTS	5
BUCKLES	ALUMINUM BUCKLES - IZY
FALL ARREST INDICATORS	YES
LANYARD KEEPERS	YES
MAX RATED LOAD	310 lbs
WEIGHT PER SIZE EAN/UPC PER SIZE	FS242IBD-S/M - 1.40kg - 5605423813418 / 626053660086 FS242IBD-L/XL - 1.45kg - 5605423813920 / 626053660543 FS242IBD-XXL - 1.50kg - 5605423813937 / 626053660550

PROFESSIONAL

FS242IBD

HARN FLEX BASIC 2D S/M



O FS242IBD - HARN FLEX BASIC 2D é um arnês de corpo inteiro desenvolvido para oferecer máxima segurança, conforto e praticidade em atividades realizadas em altura. Integrante da linha BASIC PRO, este modelo se destaca por sua versatilidade e robustez, mantendo o padrão de qualidade e proteção exigido pelos profissionais que atuam em ambientes verticais.

Sua principal característica diferenciadora em relação ao modelo FS242IB é a presença de dois pontos de ancoragem metálicos em D-ring: um localizado na região dorsal (ponto A) e outro na região do peito, oferecendo mais opções de conexão para sistemas de retenção de quedas e garantindo maior flexibilidade operacional conforme o tipo de trabalho executado.

O design é simplificado, porém eficiente, com ajuste no peito por meio de fivela IZY Quick Connect, que proporciona agilidade na colocação e retirada do equipamento. As laterais em silicone aumentam o conforto e protegem as costuras contra desgaste.

Conta ainda com fivelas de ajuste tipo mola, que permitem ajustes rápidos e seguros, além de quatro argolas laterais para transporte de ferramentas ou acessórios, facilitando o acesso a equipamentos durante a operação. Dispõe de dois pontos de posicionamento para longe, ampliando suas possibilidades de uso em diferentes cenários.

O sistema de identificação com etiqueta, número de série e QR Code garante a rastreabilidade e facilita a gestão do EPI, contribuindo para a conformidade com normas de segurança.

Ideal para profissionais que buscam um arnês completo, com dois pontos de ancoragem metálicos (dorsal e peitoral), o FS242IBD - HARN FLEX BASIC 2D oferece a combinação perfeita entre segurança, funcionalidade e conforto para trabalhos em altura.



Informação Técnica

TEMPO DE VIDA ÚTIL	10 Years
CARGA MÁXIMA	ANSI - 310lbs CSA - 310lbs OSHA - 310lbs
INSPEÇÃO	Yearly
RASTREABILIDADE	S/N RFID QR Code
NORMAS	ANSI - Z359.11-2021 CSA - Z259.10-18 OSHA - OSHA 1926.502 OSHA - OSHA 1910.140
INTRASTAT	63079098

Imagens do Produto


ESPECIFICAÇÕES

COMPONENTES METÁLICOS	ALUMÍNIO E LIGA DE AÇO
COMPONENTES TÊXTEIS	POLIÉSTER (PES)
MATERIAL	POLIÉSTER (PES)
OUTROS MATERIAIS	EVA, SILICONE, PA, PEHD E PES
TIPO DE FITA	POLIÉSTER (PES)
D-RINGS	2
PONTOS DE ANCORAGEM (A)	2
SUORTE DE FERRAMENTAS	4
CAPACIDADE MÁX. DO SUORTE DE FERRAMENTAS	5 kg
PONTOS DE AJUSTE	5
FIVELAS	FIVELAS EM ALUMÍNIO - IZY
INDICADORES DE QUEDA	SIM
SUORTE DE LONGES	SIM
CARGA MÁXIMA	140 kg
WEIGHT PER SIZE EAN/UPC PER SIZE	FS242IBD-S/M - 1.40kg - 5605423813418 / 626053660086 FS242IBD-L/XL - 1.45kg - 5605423813920 / 626053660543 FS242IBD-XXL - 1.50kg - 5605423813937 / 626053660550