



PROFESSIONAL

FS803

FILUM - ANCHOR WIRE

The FALL SAFE® FS803 consists of an 8mm galvanized steel cable, whose ends are joined by a carabiner. Works as a temporary and portable fall arrest system.



TECHNICAL INFORMATION

LIFESPAN	UNDEFINED
MAXIMUM LOAD	CE - N/A
INSPECTION	Yearly
TRACEABILITY	S/N QR Code
STANDARDS	CE - EN795:2012-B
INTRASTAT	63079098

PRODUCT PHOTOS



SPECIFICATIONS

MATERIAL Galvanized steel cable and aluminium

CLASS B

MAX STRENGTH 22kN

MAX RATED LOAD 120kg

MAX USERS NO. 1

DIMENSIONS 0.50 m to 4 m

WEIGHT PER SIZE EAN PER SIZE	FS803-0.5M - 0,25kg - 5605423420289
	FS803-4M - 2,80kg - 5605423420234
	FS803-3M - 2,60kg - 5605423420241
	FS803-2M-50004 - 2,00kg - 5605423807288
	FS803-2M - 2,00kg - 5605423420258
	FS803-2.4M - 2,30kg - 5605423801552
	FS803-1M - 0,60kg - 5605423420401
FS803-1.5M - 0,75kg - 5605423420272	



PROFESSIONAL

FS803

FILUM - ANCHOR WIRE

O FALL SAFE® FS803 é constituído por um cabo de aço galvanizado de 8mm, em que as suas extremidades são unidas por um mosquetão. Funciona como sistema antiqueda temporário e portátil.



Informação Técnica	
TEMPO DE VIDA ÚTIL	UNDEFINED
CARGA MÁXIMA	CE - N/A
INSPEÇÃO	Yearly
RASTREABILIDADE	S/N QR Code
NORMAS	CE - EN795:2012-B
INTRASTAT	63079098

Imagens do Produto



ESPECIFICAÇÕES

MATERIAL Galvanized steel cable and aluminium

CLASSE B

FORÇA MÁX 22kN

CARGA MÁXIMA 120kg

Nº MÁX UTILIZADORES 1

DIMENSÕES 0.50 m to 4 m

PESO POR TAMANHO | EAN POR TAMANHO

- FS803-0.5M - 0,25kg - 5605423420289
- FS803-4M - 2,80kg - 5605423420234
- FS803-3M - 2,60kg - 5605423420241
- FS803-2M-50004 - 2,00kg - 5605423807288
- FS803-2M - 2,00kg - 5605423420258
- FS803-2.4M - 2,30kg - 5605423801552
- FS803-1M - 0,60kg - 5605423420401
- FS803-1.5M - 0,75kg - 5605423420272