



PROFESSIONAL

FS243.01- 55

SPINDEL BLACK COMBO 1

FALL SAFE® FS243.01-55 - BLACK SPINDEL® Combo 1 is a 4-arm fall arrest harness for optimized vertical body position and support for extended hours of work with difficult access. Airflow through all layers of the harness is ensured by the new and improved Croc 2.0 padding. This innovation also allows for a lighter and more ergonomic final product, extremely comfortable for several hours in suspension. The dark colors allow it to be used in dark environments such as riggers or military-related environments.



TECHNICAL INFORMATION

LIFESPAN	10
MAXIMUM LOAD	CE - 140kg
INSPECTION	Yearly
TRACEABILITY	S/N RFID QR Code
STANDARDS	CE - EN361:2002 CE - EN358:2018 CE - EN813:2008
INTRASTAT	63079098

PRODUCT PHOTOS



SPECIFICATIONS

METAL PARTS	Aluminium, steel
TEXTILE PARTS	Polyester
OTHER COMPONENTS MATERIAL	PA6, silicone
WEBBING TYPE	PES 45mm water-repellent
D-RINGS	Front, back, ventral and side
ANCHOR POINTS (A)	5
SHOULDER PADDING	Yes - Croc Smooth Padding 3.0
LUMBAR PADDING	Yes - Croc Smooth Padding 3.0
LEG PADDING	Yes
PADDING MATERIAL	TPU, EVA, PA, high visibility mesh and fabric PES
SEAT CONNECTION POINT	Yes
TOOL HOLDERS	5
TOOL HOLDERS MAX LOAD	15kg
ADJUSTMENT POINTS	7
BUCKLES	2 ALU IZY quick connect buckles; 5 ST 3-bar buckles
FALL ARREST INDICATORS	Yes
LANYARD KEEPERS	Yes
COMPONENTS	Safety Technology - FALL SAFE INSPECTOR®
WEIGHT PER SIZE EAN PER SIZE	FS243.01-S/M-55 - 2,10kg - 5605423805659 FS243.01-LXL-55 - 2,45kg - 5605423803457



PROFESSIONAL

FS243.01- 55

SPINDEL BLACK COMBO 1

FALL SAFE® FS243.01-55 - BLACK SPINDEL® Combo 1 é um arnês de proteção contra quedas com 4 braços para posição vertical otimizada do corpo e suporte para horas de trabalho prolongadas com acesso difícil. O fluxo de ar através de todas as camadas do arnês é garantido pelo novo e aprimorado padding Croc 2.0. Esta inovação também permite um produto final mais leve e ergonômico, extremamente confortável por várias horas em suspensão. As cores escuras permitem que seja usado em ambientes escuros como riggers ou relacionados à área militar.



Informação Técnica

TEMPO DE VIDA ÚTIL	10
CARGA MÁXIMA	CE - 140kg
INSPEÇÃO	Yearly
RASTREABILIDADE	S/N RFID QR Code
NORMAS	CE - EN361:2002 CE - EN358:2018 CE - EN813:2008
INTRASTAT	63079098

Imagens do Produto



ESPECIFICAÇÕES

COMPONENTES METÁLICOS	Aluminium, steel
COMPONENTES TÊXTEIS	Polyester
OUTROS MATERIAIS	PA6, silicone
TIPO DE FITA	PES 45mm water-repellent
D-RINGS	Front, back, ventral and side
PONTOS DE ANCORAGEM (A)	5
PADDING OMBROS	Yes - Croc Smooth Padding 3.0
PADDING LOMBAR	Yes - Croc Smooth Padding 3.0
PADDING PERNA	Yes
MATERIAL DO PADDING	TPU, EVA, PA, high visibility mesh and fabric PES
PONTO LIGAÇÃO DE CADEIRA	Yes
SUPORTE DE FERRAMENTAS	5
CAPACIDADE MÁX. DO SUPORTE DE FERRAMENTAS	15kg
PONTOS DE AJUSTE	7
FIVELAS	2 ALU IZY quick connect buckles; 5 ST 3-bar buckles
INDICADORES DE QUEDA	Yes
SUPORTE DE LONGES	Yes
COMPONENTES	Tecnologia de Segurança - FALL SAFE INSPECTOR®
PESO POR TAMANHO EAN POR TAMANHO	FS243.01-S/M-55 - 2,10kg - 5605423805659 FS243.01-LXL-55 - 2,45kg - 5605423803457