

FSR02

ICY WHITE FALL SAFE SEMI STATIC ROPE - Ø11MM

The FALL SAFE® STATIC ROPES are developed with the highest quality, with a stringent quality control. The high proportion of sheath to cover ratio improves protection. Made with low stretch kernmantle, our ropes have high strength, extra resistance to abrasion, excellent UV protection as well as excellent handling and knot holding characteristics.

TECHNICAL INFORMATION

LIFESPAN	10
MAXIMUM LOAD	CE - N/A
INSPECTION	N/A
TRACEABILITY	S/N
STANDARDS	CE - EN1891:1998-A
INTRASTAT	56074919

PRODUCT PHOTOS



FALL SAFE ON LINE LDA
ZONA INDUSTRIAL DA VARZIELA, RUA B, LOTE 54, 4480-620 VILA DO CONDE
SUPPORT@FALLSAFE-ONLINE.COM | WWW.FALLSAFE-ONLINE.COM

SPECIFICATIONS

MATERIAL	CORE - PA / COVER - PES
MAX STRENGTH	35.6 kN
DIMENSIONS	Ø11mm
WEIGHT PER SIZE EAN/UPC PER SIZE	FSR02 - 0,10kg - 5605423450101

FALL SAFE ON LINE LDA
ZONA INDUSTRIAL DA VARZIELA, RUA B, LOTE 54, 4480-620 VILA DO CONDE
SUPPORT@FALLSAFE-ONLINE.COM | WWW.FALLSAFE-ONLINE.COM



FSR02

ICY WHITE FALL SAFE SEMI STATIC ROPE - Ø11MM

As cordas estáticas FALL SAFE® são desenvolvidas com a mais alta qualidade, com um rigoroso controlo de qualidade. A alta proporção de bainha melhora a proteção. Fabricadas com kernmatle elástica, as nossas cordas possuem alta resistência, resistência extra à abrasão, excelente proteção UV, além de excelentes características de manuseio e retenção de nós.

Informação Técnica

TEMPO DE VIDA ÚTIL	10
CARGA MÁXIMA	CE - N/A
INSPEÇÃO	N/A
RASTREABILIDADE	S/N
NORMAS	CE - EN1891:1998-A
INTRASTAT	56074919

Imagens do Produto



FALL SAFE ON LINE LDA
ZONA INDUSTRIAL DA VARZIELA, RUA B, LOTE 54, 4480-620 VILA DO CONDE
SUPPORT@FALLSAFE-ONLINE.COM | WWW.FALLSAFE-ONLINE.COM

ESPECIFICAÇÕES

MATERIAL	CORE - PA / COVER - PES
FORÇA MÁX	35.6 kN
DIMENSÕES	Ø11mm
WEIGHT PER SIZE EAN/UPC PER SIZE	FSR02 - 0,10kg - 5605423450101

FALL SAFE ON LINE LDA
ZONA INDUSTRIAL DA VARZIELA, RUA B, LOTE 54, 4480-620 VILA DO CONDE
SUPPORT@FALLSAFE-ONLINE.COM | WWW.FALLSAFE-ONLINE.COM