



**PROFESSIONAL**

**FS525-QS**

**ARC FLASH - Y LANYARD WITH ENERGY ABSORBER**

FS525-QS ARC FLASH is a double lanyard in accordance with standards EN354 and EN355 and ASTM F887 tested - Arc Flash environment. It is composed of an energy absorber (PES – 43mm) with Kevlar® webbing as backup, Kevlar seams, and dielectric connectors in accordance with EN362. The energy absorber has a maximum load bearing of 140kg and limits the impact forces below 6kN.



**TECHNICAL INFORMATION**

LIFESPAN	8
MAXIMUM LOAD	CE - 140kg
INSPECTION	Yearly
TRACEABILITY	S/N QR Code
STANDARDS	CE - EN354:2010 CE - EN355:2002 CE - ASTM F887-2012
INTRASTAT	56090000

**PRODUCT PHOTOS**



**SPECIFICATIONS**

MATERIAL	Kevlar®, Nomex®, Dielectric, Silicone
WEBBING TYPE	Kevlar® webbing Nomex® coated 44mm
CONNECTORS	Dielectric snap hook + Dielectric Rebar hook
MAX LENGTH	2m
ENERGY ABSORBER	Yes - up to 120 Kg
SEAMS PROTECTOR	No
SHARP EDGE TESTED	No
WEIGHT PER SIZE   EAN PER SIZE	FS525-QS-1.5M - 1.55kg - 5605423809404 FS525-QS-2M - 1.60kg - 5605423362244


**PROFESSIONAL**
**FS525-QS**
**ARC FLASH - Y LANYARD WITH ENERGY ABSORBER**

FS525-QS ARC FLASH é uma longe de progressão dupla certificada de acordo com as normas EN354 e EN355 e testada ASTM F887 - ambiente Arc Flash. É composto por um absorvedor de energia (PES – 43mm) com reforço Kevlar®, costuras Kevlar e conectores dielétricos de acordo com EN362. O absorvedor de energia tem um suporte de carga máximo de 140kg e limita as forças de impacto abaixo de 6kN.


**Informação Técnica**

TEMPO DE VIDA ÚTIL	8
CARGA MÁXIMA	CE - 140kg
INSPEÇÃO	Yearly
RASTREABILIDADE	S/N QR Code
NORMAS	CE - EN354:2010 CE - EN355:2002 CE - ASTM F887-2012
INTRASTAT	56090000

**Imagens do Produto**


**ESPECIFICAÇÕES**

MATERIAL	Kevlar®, Nomex®, Dielectric, Silicone
TIPO DE FITA	Kevlar® webbing Nomex® coated 44mm
CONECTORES	Dielectric snap hook + Dielectric Rebar hook
COMPRIMENTO MÁX	2m
ABSORBEDOR DE ENERGIA	Yes - up to 120 Kg
PROTETOR DE COSTURAS	No
TESTADO ARESTAS CORTANTES	No
PESO POR TAMANHO   EAN POR TAMANHO	FS525-QS-1.5M - 1.55kg - 5605423809404 FS525-QS-2M - 1.60kg - 5605423362244