



FS522R

EDGE TESTED - DOUBLE LANYARD WITH ENERGY ABSORBER

FS522R is a double progression lanyard (EN354, EN355). This equipment is made from 12mm PA rope and has been tested for use on cutting edges (PPE-R/11.074) on a 0.5mm edge. It has a maximum length of 2 meters and several possibilities for connector combinations on request.



TECHNICAL INFORMATION

LIFESPAN	10
MAXIMUM LOAD	CE - 140kg
INSPECTION	Yearly
TRACEABILITY	S/N QR Code
STANDARDS	CE - EN354:2010 CE - EN355:2002 CE - CNB/P/11.074
INTRASTAT	56090000

PRODUCT PHOTOS



SPECIFICATIONS

MATERIAL	PA, PES, ALU, Silicone, Polimero
ROPE TYPE	PA (core) + PES (cover) 12mm
CONNECTORS	FS820 ALU screw lock 25kN; FS821 ALU auto lock 23kN (other combinations on request)
MAX LENGTH	2m
ENERGY ABSORBER	Yes, PES - up to 140 Kg
SEAMS PROTECTOR	Yes
SHARP EDGE TESTED	Yes (PPE-R/11.074)

WEIGHT PER SIZE EAN/UPC PER SIZE	FS522R-AB-1M - 1.97kg - 5605423815573
	FS522R-1.5M - 1.62kg - 5605423753882
	FS522R-AA-1.5M - 1.62kg - 5605423321401
	FS522R-AA-2M - 1.67kg - 5605423321418
	FS522R-AB-1.5M - 1.97kg - 5605423753783
	FS522R-AC-1.5M - 1.62kg - 5605423321425
	FS522R-AC-2M - 1.67kg - 5605423321432
	FS522R-AD-2M - 1.20kg - 5605423815665
	FS522R-CB-1.5M - 1.62kg - 5605423754018
	FS522R-CC-1.5M - 1.62kg - 5605423321463
	FS522R-CC-2M - 1.67kg - 5605423321470
	FS522R-FB-2M - 1.20kg - 5605423813241
	FS522R-KB-1.5M - 1.62kg - 5605423321500
	FS522R-KB-2M - 1.67kg - 5605423321517
FS522R-TB-1.5M - 1.20kg - 5605423816105	
FS522R-AB-2M - 2.63kg - 5605423753790	



FS522R

EDGE TESTED - DOUBLE LANYARD WITH ENERGY ABSORBER

FS522R is a double progression lanyard (EN354, EN355). This equipment is made from 12mm PA rope and has been tested for use on cutting edges (PPE-R/11.074) on a 0.5mm edge. It has a maximum length of 2 meters and several possibilities for connector combinations on request.



INFORMATIONS TECHNIQUES

DURÉE DE VIE	10
CHARGE MAXIMALE	CE - 140kg
INSPECTION	Yearly
TRAÇABILITÉ	S/N QR Code
NORMES	CE - EN354:2010 CE - EN355:2002 CE - CNB/P/11.074
INTRASTAT	56090000

PHOTOS PRODUIT



SPÉCIFICATIONS

WEIGHT PER SIZE EAN/UPC PER SIZE

FS522R-AB-1M	- 1.97kg	- 5605423815573
FS522R-1.5M	- 1.62kg	- 5605423753882
FS522R-AA-1.5M	- 1.62kg	- 5605423321401
FS522R-AA-2M	- 1.67kg	- 5605423321418
FS522R-AB-1.5M	- 1.97kg	- 5605423753783
FS522R-AC-1.5M	- 1.62kg	- 5605423321425
FS522R-AC-2M	- 1.67kg	- 5605423321432
FS522R-AD-2M	- 1.20kg	- 5605423815665
FS522R-CB-1.5M	- 1.62kg	- 5605423754018
FS522R-CC-1.5M	- 1.62kg	- 5605423321463
FS522R-CC-2M	- 1.67kg	- 5605423321470
FS522R-FB-2M	- 1.20kg	- 5605423813241
FS522R-KB-1.5M	- 1.62kg	- 5605423321500
FS522R-KB-2M	- 1.67kg	- 5605423321517
FS522R-TB-1.5M	- 1.20kg	- 5605423816105
FS522R-AB-2M	- 2.63kg	- 5605423753790



FS522R

EDGE TESTED - DOUBLE LANYARD WITH ENERGY ABSORBER

FS522R is a double progression lanyard (EN354, EN355). This equipment is made from 12mm PA rope and has been tested for use on cutting edges (PPE-R/11.074) on a 0.5mm edge. It has a maximum length of 2 meters and several possibilities for connector combinations on request.



TECHNICAL INFORMATION

LIFESPAN	10
MAXIMUM LOAD	CE - 140kg
INSPECTION	Yearly
TRACEABILITY	S/N QR Code
STANDARDS	CE - EN354:2010 CE - EN355:2002 CE - CNB/P/11.074
INTRASTAT	56090000

PRODUCT PHOTOS



SPECIFICATIONS

WEIGHT PER SIZE EAN/UPC PER SIZE

FS522R-AB-1M	- 1.97kg	- 5605423815573
FS522R-1.5M	- 1.62kg	- 5605423753882
FS522R-AA-1.5M	- 1.62kg	- 5605423321401
FS522R-AA-2M	- 1.67kg	- 5605423321418
FS522R-AB-1.5M	- 1.97kg	- 5605423753783
FS522R-AC-1.5M	- 1.62kg	- 5605423321425
FS522R-AC-2M	- 1.67kg	- 5605423321432
FS522R-AD-2M	- 1.20kg	- 5605423815665
FS522R-CB-1.5M	- 1.62kg	- 5605423754018
FS522R-CC-1.5M	- 1.62kg	- 5605423321463
FS522R-CC-2M	- 1.67kg	- 5605423321470
FS522R-FB-2M	- 1.20kg	- 5605423813241
FS522R-KB-1.5M	- 1.62kg	- 5605423321500
FS522R-KB-2M	- 1.67kg	- 5605423321517
FS522R-TB-1.5M	- 1.20kg	- 5605423816105
FS522R-AB-2M	- 2.63kg	- 5605423753790



FS522R

EDGE TESTED - DOUBLE LANYARD WITH ENERGY ABSORBER

FS522R é uma lanyard de progressão dupla (EN354, EN355). Este equipamento é fabricado com corda PA de 12mm e foi testado para uso em arestas cortantes (PPE-R/11.074) numa aresta de 0.5mm. Tem um comprimento máximo de 2 metros e várias possibilidades de combinações de conectores sob consulta.



Informação Técnica

TEMPO DE VIDA ÚTIL	10
CARGA MÁXIMA	CE - 140kg
INSPEÇÃO	Yearly
RASTREABILIDADE	S/N QR Code
NORMAS	CE - EN354:2010 CE - EN355:2002 CE - CNB/P/11.074
INTRASTAT	56090000

Imagens do Produto



ESPECIFICAÇÕES

MATERIAL	PA, PES, ALU, Silicone, Polimero
TIPO DE CORDA	PA (core) + PES (cover) 12mm
CONECTORES	FS820 ALU screw lock 25kN; FS821 ALU auto lock 23kN (other combinations on request)
COMPRIMENTO MÁX	2m
ABSORBEDOR DE ENERGIA	Yes, PES - up to 140 Kg
PROTETOR DE COSTURAS	Yes
TESTADO ARESTAS CORTANTES	Yes (PPE-R/11.074)

WEIGHT PER SIZE EAN/UPC PER SIZE	FS522R-AB-1M - 1.97kg - 5605423815573
	FS522R-1.5M - 1.62kg - 5605423753882
	FS522R-AA-1.5M - 1.62kg - 5605423321401
	FS522R-AA-2M - 1.67kg - 5605423321418
	FS522R-AB-1.5M - 1.97kg - 5605423753783
	FS522R-AC-1.5M - 1.62kg - 5605423321425
	FS522R-AC-2M - 1.67kg - 5605423321432
	FS522R-AD-2M - 1.20kg - 5605423815665
	FS522R-CB-1.5M - 1.62kg - 5605423754018
	FS522R-CC-1.5M - 1.62kg - 5605423321463
	FS522R-CC-2M - 1.67kg - 5605423321470
	FS522R-FB-2M - 1.20kg - 5605423813241
	FS522R-KB-1.5M - 1.62kg - 5605423321500
	FS522R-KB-2M - 1.67kg - 5605423321517
FS522R-TB-1.5M - 1.20kg - 5605423816105	
FS522R-AB-2M - 2.63kg - 5605423753790	