



PROFESSIONAL

FS242

LITE - HARNESS

FS242 LITE is a bestseller. Extremely lightweight and easy to wear, this full body harness has multiple adjustment points and can adapt to the wearer. With a unique and innovative design, the anchorage point on the back is achieved through a loop created by the equipment's own tape, as well as the two 1/2 A on the front of the equipment. This makes it lighter. On the sides, they have two silicone plates with high impact resistance to protect the user. The shoulders of the harness are protected with Croc 3.0 padding for extra comfort, but always ensuring airflow through all layers. This equipment allows the user great mobility thanks to its design.



TECHNICAL INFORMATION

LIFESPAN	10
MAXIMUM LOAD	CE - 140kg
INSPECTION	Yearly
TRACEABILITY	S/N RFID QR Code
STANDARDS	CE - EN361:2002
INTRASTAT	63079098

PRODUCT PHOTOS



SPECIFICATIONS

METAL PARTS	Aluminium, steel
TEXTILE PARTS	Polyester
OTHER COMPONENTS MATERIAL	PA6, silicone
WEBBING TYPE	PES 45mm water-repellent
D-RINGS	Webbing loop at back, front
ANCHOR POINTS (A)	2
SHOULDER PADDING	Yes - Croc Smooth Padding 3.0
LUMBAR PADDING	No
LEG PADDING	Yes
PADDING MATERIAL	TPU, EVA, PA, high visibility mesh and fabric PES
SEAT CONNECTION POINT	No
TOOL HOLDERS	4
TOOL HOLDERS MAX LOAD	15kg
ADJUSTMENT POINTS	5
BUCKLES	2 ALU IZY quick connect buckles; 2 ST 3-bar buckles
FALL ARREST INDICATORS	Yes
LANYARD KEEPERS	Yes
WEIGHT PER SIZE EAN PER SIZE	FS242-S/M - 1,80kg - 5605423475616 FS242-L/XL - 1,90kg - 5605423802207 FS242-XXL - 2,00kg - 5605423570823



PROFESSIONAL

FS242

LITE - HARNESS

FS242 LITE é um bestseller. Extremamente leve e fácil de vestir, este arnês de corpo inteiro tem vários pontos de ajuste e consegue adaptar-se ao utilizador. Com um design único e inovador, o ponto de ancoragem nas costas é conseguido através de uma argola criada pela própria fita do equipamento, assim como os dois 1/2 A na frente do equipamento (EN361). Isto torna-o mais leve. Nas laterais tem duas placas em silicone com alta resistência ao impacto para proteção do utilizador. Os ombros do arnês são protegidos com padding Croc 3.0 para um conforto extra, mas sempre garantindo o fluxo de ar por todas as camadas. Este equipamento permite ao utilizador grande mobilidade graças ao seu design.



Informação Técnica

TEMPO DE VIDA ÚTIL	10
CARGA MÁXIMA	CE - 140kg
INSPEÇÃO	Yearly
RASTREABILIDADE	S/N RFID QR Code
NORMAS	CE - EN361:2002
INTRASTAT	63079098

Imagens do Produto



ESPECIFICAÇÕES

COMPONENTES METÁLICOS	Aluminium, steel
COMPONENTES TÊXTEIS	Polyester
OUTROS MATERIAIS	PA6, silicone
TIPO DE FITA	PES 45mm water-repellent
D-RINGS	Webbing loop at back, front
PONTOS DE ANCORAGEM (A)	2
PADDING OMBROS	Yes - Croc Smooth Padding 3.0
PADDING LOMBAR	No
PADDING PERNA	Yes
MATERIAL DO PADDING	TPU, EVA, PA, high visibility mesh and fabric PES
PONTO LIGAÇÃO DE CADEIRA	No
SUPORTE DE FERRAMENTAS	4
CAPACIDADE MÁX. DO SUPORTE DE FERRAMENTAS	15kg
PONTOS DE AJUSTE	5
FIVELAS	2 ALU IZY quick connect buckles; 2 ST 3-bar buckles
INDICADORES DE QUEDA	Yes
SUPORTE DE LONGES	Yes
PESO POR TAMANHO EAN POR TAMANHO	FS242-S/M - 1,80kg - 5605423475616 FS242-L/XL - 1,90kg - 5605423802207 FS242-XXL - 2,00kg - 5605423570823