

PROFESSIONAL

FS883

TOGGLE ANCHOR



FALL SAFE® FS883 is a versatile, portable steel anchor used exclusively for fall protection. The toggle lock can be placed on horizontal, vertical and overhead/ceiling surfaces. It has a 20mm expander screw.



TECHNICAL INFORMATION

| | |
|--------------|-------------------|
| LIFESPAN | UNDEFINED |
| MAXIMUM LOAD | CE - N/A |
| INSPECTION | Yearly |
| TRACEABILITY | S/N |
| STANDARDS | CE - EN795:2012-B |
| INTRASTAT | 73269098 |

PRODUCT PHOTOS



SPECIFICATIONS

| | |
|--------------------------------|--------------------------------|
| MATERIAL | Steel alloy |
| CLASS | B |
| MAX STRENGTH | 12kN |
| MAX RATED LOAD | 140kg |
| MAX USERS NO. | 1 |
| WEIGHT PER SIZE EAN PER SIZE | FS883 - 0.27kg - 5605423820348 |

PROFESSIONAL

FS883

TOGGLE ANCHOR



FALL SAFE® FS883 é uma ancoragem versátil, portátil de aço, usada exclusivamente para proteção contra quedas. A trava de alternância pode ser colocada em superfícies horizontais, verticais e superiores/teto. Possui um parafuso expansor de 20mm.



Informação Técnica

| | |
|--------------------|-------------------|
| TEMPO DE VIDA ÚTIL | UNDEFINED |
| CARGA MÁXIMA | CE - N/A |
| INSPEÇÃO | Yearly |
| RASTREABILIDADE | S/N |
| NORMAS | CE - EN795:2012-B |
| INTRASTAT | 73269098 |

Imagens do Produto



ESPECIFICAÇÕES

| | |
|------------------------------------|--------------------------------|
| MATERIAL | Steel alloy |
| CLASSE | B |
| FORÇA MÁX | 12kN |
| CARGA MÁXIMA | 140kg |
| Nº MÁX UTILIZADORES | 1 |
| PESO POR TAMANHO EAN POR TAMANHO | FS883 - 0.27kg - 5605423820348 |