

PROFESSIONAL

FS973

AUTO - EVACUATION SYSTEM AUTOMATIC



FS973 is a rescue kit with a controlled descent device. During the descent process, the centrifugal brake keeps the device at a constant speed during the entire descent. With the help of the new deviation point on the device, the descent speed can be regulated. This device is ideal device for self-rescue / multiple evacuations or for training measures. The kit also includes a transport bag, an FS800 anchor strap and a telescopic pole.



TECHNICAL INFORMATION

LIFESPAN	10
MAXIMUM LOAD	N/A
INSPECTION	Yearly
TRACEABILITY	S/N QR Code
STANDARDS	N/A
INTRASTAT	63079098

PRODUCT PHOTOS



SPECIFICATIONS

METAL PARTS	Aluminium
OTHER COMPONENTS MATERIAL	PA, Silicone
WEBBING TYPE	PES Hi-Vis waterproof 44 mm
ROPE TYPE	Kernmantle rope Ø 10.5 mm
DEVICE	Resistant and low-maintenance descent device with swivel with ball bearing
CONNECTORS	1x steel screw lock connector + 2x hooks
MAX LENGTH	200 m
MAX RATED LOAD	140 kg
HOUSING	Seawater-resistant aluminium housing
COMPONENTS	1x 1 x PES webbing anchor sling - 25mm2 x Personal rescue sling 1 x ALU karabiner 1 x Winch system 1 x Carrying bag

WEIGHT PER SIZE | EAN PER SIZE

FS973-10M	- 1.80kg	- 5605423430714
FS973-100M	- 8.50kg	- 5605423752335
FS973-105M	- 8.80kg	- 5605423430479
FS973-1-100M	- 1.80kg	- 5605423802832
FS973-20M	- 2.60kg	- 5605423430561
FS973-2-30M	- 2.60kg	- 5605423437416
FS973-30M	- 4.20kg	- 5605423430684
FS973-40M	- 4.80kg	- 5605423821703
FS973-50M	- 5.50kg	- 5605423800852
FS973-60M	- 10.00kg	- 5605423430349
FS973-80M	- 7.20kg	- 5605423752342
FS973-90M	- 7.70kg	- 5605423430691
FS973-VP-60M	- 2.60kg	- 5605423805017



PROFESSIONAL

FS973

AUTO - EVACUATION SYSTEM AUTOMATIC

FS973 é um kit de resgate com dispositivo de descida controlada. Durante o processo de descida, o travão centrífugo mantém o dispositivo a uma velocidade constante durante toda a descida. Com a ajuda do novo ponto de desvio no dispositivo, a velocidade de descida pode ser regulada. Este dispositivo é ideal para auto-resgate ou evacuações. O kit inclui ainda um saco de transporte, uma cinta de ancoragem FS800 e uma vara telescópica.



Informação Técnica

TEMPO DE VIDA ÚTIL	10
CARGA MÁXIMA	N/A
INSPEÇÃO	Yearly
RASTREABILIDADE	S/N QR Code
NORMAS	N/A
INTRASTAT	63079098

Imagens do Produto



ESPECIFICAÇÕES

COMPONENTES METÁLICOS	Alumínio
TIPO DE CORDA	Corda Kernmantle Ø 10.5 mm
DISPOSITIVO	Dispositivo de descida resistente e de baixa manutenção com giro com rolamento de esferas
CONECTORES	1x conector de aço + 2x ganchos
COMPRIMENTO MÁX	200 m
CARGA MÁXIMA	140 kg
INVÓLUCRO	Carçaça de alumínio resistente à água do mar

PESO POR TAMANHO | EAN POR TAMANHO

FS973-10M - 1.80kg - 5605423430714
FS973-100M - 8.50kg - 5605423752335
FS973-105M - 8.80kg - 5605423430479
FS973-1-100M - 1.80kg - 5605423802832
FS973-20M - 2.60kg - 5605423430561
FS973-2-30M - 2.60kg - 5605423437416
FS973-30M - 4.20kg - 5605423430684
FS973-40M - 4.80kg - 5605423821703
FS973-50M - 5.50kg - 5605423800852
FS973-60M - 10.00kg - 5605423430349
FS973-80M - 7.20kg - 5605423752342
FS973-90M - 7.70kg - 5605423430691
FS973-VP-60M - 2.60kg - 5605423805017