



PROFESSIONAL

FS976

RESCUE WINCH LUG

The FALL SAFE® FS976 - RESCUE WINCH is a rescue winch with lifting and lowering facility, maximum rated load of 150kg, suitable to use for 1 person only, and maximum length of 20 meters. It should be used together with FS975 - Tri One Rescue Tripod, and shall only be used for rescue purposes. FS976 includes a auto-brake system. Gear ratio 5:1. Includes bracket to attach to Tripod FS975. Rescue winch should not be used for fall arrest purposes. The FS976 is not suitable for use over a sharp edge and has not been edge tested.

TECHNICAL INFORMATION

LIFESPAN	UNDEFINED
MAXIMUM LOAD	CE - 150kg
INSPECTION	Yearly
TRACEABILITY	S/N
STANDARDS	CE - EN795:2012-B CE - EN1496:2006-A
INTRASTAT	84798997

PRODUCT PHOTOS



SPECIFICATIONS

ROPE TYPE	STEEL WIRE DIA. 5MM
CONNECTORS	SWIVEL HOOK
MAX LENGTH	20M
ENERGY ABSORBER	NO
SHARP EDGE TESTED	NO
MAX RATED LOAD	150KG
MAX USERS NO.	1
HOUSING	STEEL
CHASSIS	STEEL
LENGTH	20M
CAPACITY	150KG
DIMENSIONS	247MM X 203MM X 283MM
WEIGHT PER SIZE EAN PER SIZE	FS976 - 11,00kg - 5605423460711

PROFESSIONAL

FS976

RESCUE WINCH LUG



FALL SAFE® FS976 - RESCUE WINCH é um guincho de resgate com facilidade de elevação e abaixamento com carga nominal máxima de 150kg para ser utilizado apenas por 1 pessoa, comprimento máximo de 20 metros.

Deve ser usado em conjunto com o Tripé de Resgate FS975 - Tri One, e deve ser usado apenas para fins de resgate. FS976 inclui um sistema de travão automático. Relação de transmissão 5:1. Inclui suporte para instalar no tripé FS975. O guincho de resgate não deve ser usado para fins de prevenção de quedas. O FS976 não é adequado para uso em arestas vivas e não foi testado em arestas.

Informação Técnica

TEMPO DE VIDA ÚTIL	UNDEFINED
CARGA MÁXIMA	CE - 150kg
INSPEÇÃO	Yearly
RASTREABILIDADE	S/N
NORMAS	CE - EN795:2012-B CE - EN1496:2006-A
INTRASTAT	84798997

Imagens do Produto



ESPECIFICAÇÕES

TIPO DE CORDA	FIO DE AÇO DIÂMETRO. 5MM
CONECTORES	ELO GIRATÓRIO
COMPRIMENTO MÁX	20M
ABSORBEDOR DE ENERGIA	Não
TESTADO ARESTAS CORTANTES	Não
CARGA MÁXIMA	150KG
Nº MÁX UTILIZADORES	1
INVÓLUCRO	Aço
CHASSIS	Aço
COMPRIMENTO	20M
CAPACIDADE	150KG
DIMENSÕES	247MM X 203MM X 283MM
PESO POR TAMANHO EAN POR TAMANHO	FS976 - 11,00kg - 5605423460711