



BASIC

FS052H

LANY - WORK POSITIONING LANYARD

FALL SAFE® FS052H - LANY is a positioning lanyard, easy to use and adjust with one hand. The steel adjustment device allows precise length adjustment. A positioning lanyard should be used to prevent a user from falling when accessing hazardous areas.



TECHNICAL INFORMATION

LIFESPAN	10
MAXIMUM LOAD	CE - 140kg
INSPECTION	Yearly
TRACEABILITY	S/N RFID QR Code
STANDARDS	CE - EN358:2018
INTRASTAT	56090000

PRODUCT PHOTOS



SPECIFICATIONS

MATERIAL	PES, steel alloy
ROPE TYPE	Polyamide DB rope Ø 16mm black
CONNECTORS	FS802 screw lock 25kN; FS825 auto lock 23kN (other combinations on request)
MAX LENGTH	5m
ENERGY ABSORBER	No
SEAMS PROTECTOR	Yes
SHARP EDGE TESTED	No
WEIGHT PER SIZE EAN/UPC PER SIZE	FS052H-2M - 0.95kg - 5605423300277 FS052H-3M - 1.10kg - 5605423300260 FS052H-4M - 1.40kg - 5605423300253 FS052H-5M - 1.60kg - 5605423300246



BASIC

FS052H

LANY - WORK POSITIONING LANYARD

FALL SAFE® FS052H - LANY is a positioning lanyard, easy to use and adjust with one hand. The steel adjustment device allows precise length adjustment. A positioning lanyard should be used to prevent a user from falling when accessing hazardous areas.



INFORMATIONS TECHNIQUES

DURÉE DE VIE	10
CHARGE MAXIMALE	CE - 140kg
INSPECTION	Yearly
TRAÇABILITÉ	S/N RFID QR Code
NORMES	CE - EN358:2018
INTRASTAT	56090000

PHOTOS PRODUIT



SPÉCIFICATIONS

WEIGHT PER SIZE EAN/UPC PER SIZE

FS052H-2M	- 0.95kg	- 5605423300277
FS052H-3M	- 1.10kg	- 5605423300260
FS052H-4M	- 1.40kg	- 5605423300253
FS052H-5M	- 1.60kg	- 5605423300246



BASIC

FS052H

LANY - WORK POSITIONING LANYARD

FALL SAFE® FS052H - LANY é uma longe de posicionamento, fácil de usar e de ajustar com uma mão. O dispositivo de ajuste em aço permite um ajuste preciso do comprimento. Uma longe de posicionamento deve ser usada para impedir que um utilizador sofra uma queda no acesso a áreas de risco.



Informação Técnica

TEMPO DE VIDA ÚTIL	10
CARGA MÁXIMA	CE - 140kg
INSPEÇÃO	Yearly
RASTREABILIDADE	S/N RFID QR Code
NORMAS	CE - EN358:2018
INTRASTAT	56090000

Imagens do Produto



ESPECIFICAÇÕES

MATERIAL	PES, liga de aço
TIPO DE CORDA	Corda de poliamida DB Ø 16 MM preto
CONECTORES	FS802 bloqueio por parafuso 25 kN; FS825 bloqueio automático 23 kN (outras combinações a pedido)
COMPRIMENTO MÁX	5m
ABSORBEDOR DE ENERGIA	Não
PROTETOR DE COSTURAS	Sim
TESTADO ARESTAS CORTANTES	Não
WEIGHT PER SIZE EAN/UPC PER SIZE	FS052H-2M - 0.95kg - 5605423300277 FS052H-3M - 1.10kg - 5605423300260 FS052H-4M - 1.40kg - 5605423300253 FS052H-5M - 1.60kg - 5605423300246