



**PROFESSIONAL**

**FS249**

**ATEX - HARNESS**

FS249 ATEX is a full body harness specially developed for extreme Atex environment where explosive atmosphere exists. It is made with polyester anti-static webbing and it is an ultra-light and adjustable harness. It has an aluminum ring on the back (A - EN361) and two front loops (1/2 A + 1/2 A - EN361). The buckles are made of quick-release aluminum and provide the user with 3 different adjustment points for easy adjustment.



**TECHNICAL INFORMATION**

LIFESPAN	8
MAXIMUM LOAD	CE - 140kg
INSPECTION	Yearly
TRACEABILITY	S/N QR Code
STANDARDS	CE - EN361:2002 CE - EN60079-0:2012+A11:2013
INTRASTAT	63079098

**PRODUCT PHOTOS**



**SPECIFICATIONS**

METAL PARTS	Aluminium
TEXTILE PARTS	Anti-static polyester
OTHER COMPONENTS MATERIAL	Polímero
WEBBING TYPE	PES Anti-static 45mm
D-RINGS	ALU d-ring at back, loops on front
ANCHOR POINTS (A)	2
SHOULDER PADDING	No
LUMBAR PADDING	No
LEG PADDING	No
SEAT CONNECTION POINT	No
TOOL HOLDERS	No
TOOL HOLDERS MAX LOAD	15 kg
ADJUSTMENT POINTS	3
BUCKLES	3 ALU IZY buckles
FALL ARREST INDICATORS	Yes
LANYARD KEEPERS	No
WEIGHT PER SIZE   EAN PER SIZE	FS249-S/M - 1.10kg - 5605423571332 FS249-L/XL - 1.34kg - 5605423571295 FS249-XXL - 1.40kg - 5605423571349



**PROFESSIONAL**

**FS249**

**ATEX - HARNESS**

FS249 ATEX é um arnês de corpo inteiro especialmente desenvolvido para ambiente extremo ATEX, onde exista atmosfera explosiva. É fabricado com fitas antiestáticas de poliéster e é um arnês ultra-leve e ajustável. Tem nas costas um anel em alumínio (A - EN361) e dois loops frontais (1/2 A + 1/2 A - EN361). As fivelas são em alumínio de aperto rápido e fornece ao utilizador 3 diferentes pontos de ajuste para fácil adaptação.



**Informação Técnica**

TEMPO DE VIDA ÚTIL	8
CARGA MÁXIMA	CE - 140kg
INSPEÇÃO	Yearly
RASTREABILIDADE	S/N QR Code
NORMAS	CE - EN361:2002 CE - EN60079-0:2012+A11:2013
INTRASTAT	63079098

**Imagens do Produto**



**ESPECIFICAÇÕES**

COMPONENTES METÁLICOS	Aluminium
COMPONENTES TÊXTEIS	Anti-static polyester
OUTROS MATERIAIS	Polímero
TIPO DE FITA	PES Anti-static 45mm
D-RINGS	ALU d-ring at back, loops on front
PONTOS DE ANCORAGEM (A)	2
PADDING OMBROS	No
PADDING LOMBAR	No
PADDING PERNA	No
PONTO LIGAÇÃO DE CADEIRA	No
SUPORTE DE FERRAMENTAS	No
CAPACIDADE MÁX. DO SUPORTE DE FERRAMENTAS	15 kg
PONTOS DE AJUSTE	3
FIVELAS	3 ALU IZY buckles
INDICADORES DE QUEDA	Yes
SUPORTE DE LONGES	No
PESO POR TAMANHO   EAN POR TAMANHO	FS249-S/M - 1.10kg - 5605423571332 FS249-L/XL - 1.34kg - 5605423571295 FS249-XXL - 1.40kg - 5605423571349