



FS083

MAX PRO WP LANYARD

The FALL SAFE® FS083 - MAX PRO WP LANYARD is an easily adjustable positioning lanyard that can be operated with one hand. The new MAX PRO FS33382 device is certified to the latest European standard EN358, tested through dynamic and static tests up to 15kN, and tested for corrosion resistance with 48 hours of salt spray. The string can be replaced with easy instructions and the length of the string can be adjusted with the thumb knob and the larger lever. This device is also rescue compatible, making it possible to lower the rope in an emergency with the manual lever, a particular advantage when working on wooden poles and steel masts. The FS083 is made from FALL SAFE® professional 11mm static rope and its ends are protected by a plastic sheath. A positioning rope must be used to prevent the user from falling when accessing hazardous areas.



TECHNICAL INFORMATION

LIFESPAN	10
MAXIMUM LOAD	CE - 140kg
INSPECTION	N/A
TRACEABILITY	N/A S/N
STANDARDS	CE - EN358:2018 CE - EN365:2004
INTRASTAT	56090000

PRODUCT PHOTOS



SPECIFICATIONS

MATERIAL	PES and ALU
ROPE TYPE	PA (core) + PES (cover) static rope - Ø 11 mm
DEVICE	Max Pro
CONNECTORS	FS33573 screw lock 25kN; FS33562 auto lock 30kN (other combinations on request)
MAX LENGTH	5m
ENERGY ABSORBER	No
SEAMS PROTECTOR	Yes
SHARP EDGE TESTED	No
WEIGHT PER SIZE EAN/UPC PER SIZE	FS083-2M - 1.20kg - 5605423803648 FS083-2M-ICY - 1.20kg - 5605423808995 FS083-3M - 1.30kg - 5605423803952 FS083-4M - 1.40kg - 5605423803969 FS083-5M - 1.50kg - 5605423805437



FS083

MAX PRO WP LANYARD

The FALL SAFE® FS083 - MAX PRO WP LANYARD is an easily adjustable positioning lanyard that can be operated with one hand. The new MAX PRO FS33382 device is certified to the latest European standard EN358, tested through dynamic and static tests up to 15kN, and tested for corrosion resistance with 48 hours of salt spray. The string can be replaced with easy instructions and the length of the string can be adjusted with the thumb knob and the larger lever. This device is also rescue compatible, making it possible to lower the rope in an emergency with the manual lever, a particular advantage when working on wooden poles and steel masts. The FS083 is made from FALL SAFE® professional 11mm static rope and its ends are protected by a plastic sheath. A positioning rope must be used to prevent the user from falling when accessing hazardous areas.



INFORMATIONS TECHNIQUES

DURÉE DE VIE	10
CHARGE MAXIMALE	CE - 140kg
INSPECTION	N/A
TRAÇABILITÉ	N/A S/N
NORMES	CE - EN358:2018 CE - EN365:2004
INTRASTAT	56090000

PHOTOS PRODUIT



SPÉCIFICATIONS

WEIGHT PER SIZE EAN/UPC PER SIZE

FS083-2M	- 1.20kg	- 5605423803648
FS083-2M-ICY	- 1.20kg	- 5605423808995
FS083-3M	- 1.30kg	- 5605423803952
FS083-4M	- 1.40kg	- 5605423803969
FS083-5M	- 1.50kg	- 5605423805437



FS083

MAX PRO WP LANYARD

The FALL SAFE® FS083 - MAX PRO WP LANYARD is an easily adjustable positioning lanyard that can be operated with one hand. The new MAX PRO FS33382 device is certified to the latest European standard EN358, tested through dynamic and static tests up to 15kN, and tested for corrosion resistance with 48 hours of salt spray. The string can be replaced with easy instructions and the length of the string can be adjusted with the thumb knob and the larger lever. This device is also rescue compatible, making it possible to lower the rope in an emergency with the manual lever, a particular advantage when working on wooden poles and steel masts. The FS083 is made from FALL SAFE® professional 11mm static rope and its ends are protected by a plastic sheath. A positioning rope must be used to prevent the user from falling when accessing hazardous areas.



TECHNICAL INFORMATION

LIFESPAN	10
MAXIMUM LOAD	CE - 140kg
INSPECTION	N/A
TRACEABILITY	N/A S/N
STANDARDS	CE - EN358:2018 CE - EN365:2004
INTRASTAT	56090000

PRODUCT PHOTOS



SPECIFICATIONS

WEIGHT PER SIZE EAN/UPC PER SIZE

FS083-2M	- 1.20kg	- 5605423803648
FS083-2M-ICY	- 1.20kg	- 5605423808995
FS083-3M	- 1.30kg	- 5605423803952
FS083-4M	- 1.40kg	- 5605423803969
FS083-5M	- 1.50kg	- 5605423805437



FS083

MAX PRO WP LANYARD

O FALL SAFE® FS083 - MAX PRO WP LANYARD é uma longe de posicionamento com ajuste fácil que pode ser operada com uma mão. O novo dispositivo MAX PRO FS33382 é certificado pela mais recente norma europeia EN358, testado através de testes dinâmicos e estáticos até 15kN, testado à resistência à corrosão com 48 horas de pulverização de sal. A corda pode ser substituída com instruções fáceis e o comprimento da corda pode ser ajustado com o botão do polegar e a alavanca maior. Este dispositivo também é compatível com resgate, sendo possível descer a corda em emergência com a alavanca manual, vantagem particular ao trabalhar em postes de madeira e mastros de aço. O FS083 é fabricado com corda estática profissional de 11mm da FALL SAFE® e as suas extremidades são protegidas por uma bainha de plástico. Uma corda de posicionamento deve ser usado para impedir que o utilizador sofra uma queda quando acede a áreas de risco.



Informação Técnica

TEMPO DE VIDA ÚTIL	10
CARGA MÁXIMA	CE - 140kg
INSPEÇÃO	N/A
RASTREABILIDADE	N/A S/N
NORMAS	CE - EN358:2018 CE - EN365:2004
INTRASTAT	56090000

Imagens do Produto



ESPECIFICAÇÕES

MATERIAL	PES, Alumínio
TIPO DE CORDA	Corda estática PA (núcleo) + PES (revestimento) - Ø 11 mm
DISPOSITIVO	Max Pro
CONECTORES	FS333573 screw lock 25kN; FS33562 auto lock 30kN (outras combinações sob consulta)
COMPRIMENTO MÁX	5m
ABSORBEDOR DE ENERGIA	Não
PROTETOR DE COSTURAS	Sim
TESTADO ARESTAS CORTANTES	Não
WEIGHT PER SIZE EAN/UPC PER SIZE	FS083-2M - 1.20kg - 5605423803648 FS083-2M-ICY - 1.20kg - 5605423808995 FS083-3M - 1.30kg - 5605423803952 FS083-4M - 1.40kg - 5605423803969 FS083-5M - 1.50kg - 5605423805437