



FS525-QS

ARC FLASH - Y LANYARD WITH ENERGY ABSORBER

FS525-QS ARC FLASH is a double lanyard in accordance with standards EN354 and EN355 and ASTM F887 tested - Arc Flash environment. It is composed of an energy absorber (PES – 43mm) with Kevlar® webbing as backup, Kevlar seams, and dielectric connectors in accordance with EN362. The energy absorber has a maximum load bearing of 140kg and limits the impact forces below 6kN.



TECHNICAL INFORMATION

LIFESPAN	8
MAXIMUM LOAD	CE - 140kg
INSPECTION	Yearly
TRACEABILITY	N/A S/N QR Code
STANDARDS	CE - EN354:2010 CE - EN355:2002 CE - ASTM F887-2012 (TESTED) CE - EN365:2004
INTRASTAT	56090000

PRODUCT PHOTOS



SPECIFICATIONS

MATERIAL	Kevlar®, Nomex®, Dielectric, Silicone
WEBBING TYPE	Kevlar® webbing Nomex® coated 44mm
CONNECTORS	Dielectric snap hook + Dielectric Rebar hook
MAX LENGTH	2m
ENERGY ABSORBER	Yes
SEAMS PROTECTOR	No
SHARP EDGE TESTED	No
WEIGHT PER SIZE EAN/UPC PER SIZE	FS525-QS-1.5M - 1.55kg - 5605423815580 FS525-QS-2M - 1.60kg - 5605423362244



FS525-QS

ARC FLASH - Y LANYARD WITH ENERGY ABSORBER

FS525-QS ARC FLASH is a double lanyard in accordance with standards EN354 and EN355 and ASTM F887 tested - Arc Flash environment. It is composed of an energy absorber (PES – 43mm) with Kevlar® webbing as backup, Kevlar seams, and dielectric connectors in accordance with EN362. The energy absorber has a maximum load bearing of 140kg and limits the impact forces below 6kN.



TECHNICAL INFORMATION

LIFESPAN	8
MAXIMUM LOAD	CE - 140kg
INSPECTION	Yearly
TRACEABILITY	N/A S/N QR Code
STANDARDS	CE - EN354:2010 CE - EN355:2002 CE - ASTM F887-2012 (TESTED) CE - EN365:2004
INTRASTAT	56090000

PRODUCT PHOTOS



SPECIFICATIONS

WEIGHT PER SIZE EAN/UPC PER SIZE

FS525-QS-1.5M - 1.55kg - 5605423815580
FS525-QS-2M - 1.60kg - 5605423362244



FS525-QS

ARC FLASH - Y LANYARD WITH ENERGY ABSORBER

FS525-QS ARC FLASH is a double lanyard in accordance with standards EN354 and EN355 and ASTM F887 tested - Arc Flash environment. It is composed of an energy absorber (PES – 43mm) with Kevlar® webbing as backup, Kevlar seams, and dielectric connectors in accordance with EN362. The energy absorber has a maximum load bearing of 140kg and limits the impact forces below 6kN.



INFORMATIONS TECHNIQUES

DURÉE DE VIE	8
CHARGE MAXIMALE	CE - 140kg
INSPECTION	Yearly
TRAÇABILITÉ	N/A S/N QR Code
NORMES	CE - EN354:2010 CE - EN355:2002 CE - ASTM F887-2012 (TESTED) CE - EN365:2004
INTRASTAT	56090000

PHOTOS PRODUIT



SPÉCIFICATIONS

WEIGHT PER SIZE EAN/UPC PER SIZE

FS525-QS-1.5M - 1.55kg - 5605423815580
FS525-QS-2M - 1.60kg - 5605423362244



FS525-QS

ARC FLASH - Y LANYARD WITH ENERGY ABSORBER

FS525-QS ARC FLASH é uma longe de progressão dupla certificada de acordo com as normas EN354 e EN355 e testada ASTM F887 - ambiente Arc Flash. É composto por um absorvedor de energia (PES – 43mm) com reforço Kevlar®, costuras Kevlar e conectores dielétricos de acordo com EN362. O absorvedor de energia tem um suporte de carga máximo de 140kg e limita as forças de impacto abaixo de 6kN.



Informação Técnica

TEMPO DE VIDA ÚTIL	8
CARGA MÁXIMA	CE - 140kg
INSPEÇÃO	Yearly
RASTREABILIDADE	N/A S/N QR Code
NORMAS	CE - EN354:2010 CE - EN355:2002 CE - ASTM F887-2012 (TESTED) CE - EN365:2004
INTRASTAT	56090000

Imagens do Produto



ESPECIFICAÇÕES

MATERIAL	Kevlar®, Nomex®, Dielectric, Silicone
TIPO DE FITA	Kevlar® webbing Nomex® coated 44mm
CONECTORES	Dielectric snap hook + Dielectric Rebar hook
COMPRIMENTO MÁX	2m
ABSORBEDOR DE ENERGIA	Yes
PROTETOR DE COSTURAS	No
TESTADO ARESTAS CORTANTES	No
WEIGHT PER SIZE EAN/UPC PER SIZE	FS525-QS-1.5M - 1.55kg - 5605423815580 FS525-QS-2M - 1.60kg - 5605423362244