

PROFESSIONAL

FS242-B

LITE BELT



FS242-B LITE belt is made of high-visibility, water-repellent polyester. Allows a quick connection to the harness (compatible with FS242 and FS242EVO). It has two D-rings on the side for positioning (EN358) and an IZY quick connect buckle for equally easy and quick adjustment. It has 3 tool holding points, each with a maximum load of 15kg. This harness has Croc 3.0 padding which makes it lightweight and breathable.



TECHNICAL INFORMATION

LIFESPAN	10
MAXIMUM LOAD	CE - 140kg
INSPECTION	Yearly
TRACEABILITY	S/N RFID QR Code
STANDARDS	CE - EN358:2018
INTRASTAT	63079098

PRODUCT PHOTOS



SPECIFICATIONS

METAL PARTS	Aluminium
TEXTILE PARTS	Polyester
OTHER COMPONENTS MATERIAL	Silicone
WEBBING TYPE	PES webbing 45mm high visibility water repellent
D-RINGS	ALU D-rings on side
ANCHOR POINTS (A)	2
LUMBAR PADDING	Yes - Croc Smooth Pressure Padding 3.0
PADDING MATERIAL	TPU, EVA, PA, high visibility mesh and fabric PES
SEAT CONNECTION POINT	No
TOOL HOLDERS	3
TOOL HOLDERS MAX LOAD	15 kg
ADJUSTMENT POINTS	1
BUCKLES	ALU IZY quick connect buckle
FALL ARREST INDICATORS	No
WEIGHT PER SIZE EAN/UPC PER SIZE	FS242-B-S/M - 1.10kg - 5605423000771 FS242-B-L/XL - 1.27kg - 5605423571110 FS242-B-XXL - 1.44kg - 5605423801033

PROFESSIONAL

FS242-B

LITE BELT



FS242-B LITE belt is made of high-visibility, water-repellent polyester. Allows a quick connection to the harness (compatible with FS242 and FS242EVO). It has two D-rings on the side for positioning (EN358) and an IZY quick connect buckle for equally easy and quick adjustment. It has 3 tool holding points, each with a maximum load of 15kg. This harness has Croc 3.0 padding which makes it lightweight and breathable.



INFORMATIONS TECHNIQUES

DURÉE DE VIE	10
CHARGE MAXIMALE	CE - 140kg
INSPECTION	Yearly
TRAÇABILITÉ	S/N RFID QR Code
NORMES	CE - EN358:2018
INTRASTAT	63079098

PHOTOS PRODUIT



SPÉCIFICATIONS

WEIGHT PER SIZE EAN/UPC PER SIZE

FS242-B-S/M - 1.10kg - 5605423000771

FS242-B-L/XL - 1.27kg - 5605423571110

FS242-B-XXL - 1.44kg - 5605423801033

PROFESSIONAL

FS242-B

LITE BELT



O cinto FS242-B LITE é fabricado em poliéster de alta visibilidade e repelente à água. Permite uma conexão rápida ao arnês (compatível com FS242 e FS242EVO). Tem dois anéis D na lateral para posicionamento (EN358), fivela de aperto rápido IZY quick connect para igual fácil e rápido ajuste. Possui 3 pontos de suporte de ferramentas, cada um deles com uma carga máxima de 15kg. Este arnês tem padding Croc 3.0 sendo um equipamento leve e respirável.



Informação Técnica

TEMPO DE VIDA ÚTIL	10
CARGA MÁXIMA	CE - 140kg
INSPEÇÃO	Yearly
RASTREABILIDADE	S/N RFID QR Code
NORMAS	CE - EN358:2018
INTRASTAT	63079098

Imagens do Produto



ESPECIFICAÇÕES

COMPONENTES METÁLICOS	Alumínio
COMPONENTES TÊXTEIS	Poliéster
OUTROS MATERIAIS	Silicone
TIPO DE FITA	PES de 45 mm de alta visibilidade repelente de água
D-RINGS	D-rings ALU laterais
PONTOS DE ANCORAGEM (A)	2
PADDING LOMBAR	Sim - Croc Smooth Pressure Padding 3.0
MATERIAL DO PADDING	TPU, EVA, PA, high visibility mesh and fabric PES
PONTO LIGAÇÃO DE CADEIRA	Não
SUPORTE DE FERRAMENTAS	3
CAPACIDADE MÁX. DO SUPORTE DE FERRAMENTAS	15 kg
PONTOS DE AJUSTE	1
FIVELAS	ALU IZY quick connect buckle
INDICADORES DE QUEDA	Não
WEIGHT PER SIZE EAN/UPC PER SIZE	FS242-B-S/M - 1.10kg - 5605423000771 FS242-B-L/XL - 1.27kg - 5605423571110 FS242-B-XXL - 1.44kg - 5605423801033