



PROFESSIONAL

FS973

AUTO - EVACUATION SYSTEM AUTOMATIC

FALL SAFE® FS973 - AUTO EVACUATION SYSTEM is a compact, stable size and low weight device with automatic speed regulation (approx. 1,5m/s). The brake is controlled by centrifugal forces to keep the speed constant during the entire descend process. The device is resistant to wear, cold and corrosion and does not cause any wear or damage to the rope.

The kit also includes 2 personal rescue slings, 1 PES webbing (25mm) anchor sling and 1 carrying bag for storage.



TECHNICAL INFORMATION

LIFESPAN	10
MAXIMUM LOAD	N/A
INSPECTION	Yearly
TRACEABILITY	S/N QR Code
STANDARDS	N/A
INTRASTAT	63079098

PRODUCT PHOTOS



SPECIFICATIONS

METAL PARTS Aluminium, Steel

TEXTILE PARTS Polyester

OTHER COMPONENTS MATERIAL PA, Silicone

WEBBING TYPE PES Hi-Vis waterproof 44 mm

ROPE TYPE PA static rope 10.5 mm

DEVICE Device with automatic speed regulation

CONNECTORS 1x FS820 ALU screw lock 25kN + 2x hooks

COMPONENTS
 1 x PES webbing anchor sling - 25mm
 2 x Personal rescue sling
 1 x ALU karabiner
 1 x Winch system
 1 x Carrying bag

WEIGHT PER SIZE | EAN PER SIZE

FS973-10M - 1,80kg - 5605423430714
FS973-100M - 8,50kg - 5605423752335
FS973-105M - 8,80kg - 5605423430479
FS973-1-100M - 1,80kg - 5605423802832
FS973-20M - 2,60kg - 5605423430561
FS973-2-30M - 2,60kg - 5605423437416
FS973-30M - 4,20kg - 5605423430684
FS973-40M - 4,80kg - 5605423821703
FS973-50M - 5,50kg - 5605423800852
FS973-60M - 10,00kg - 5605423430349
FS973-80M - 7,20kg - 5605423752342
FS973-90M - 7,70kg - 5605423430691
FS973-VP-60M - 2,60kg - 5605423805017


PROFESSIONAL
FS973
AUTO - EVACUATION SYSTEM AUTOMATIC

FALL SAFE® FS973 - AUTO EVACUATION SYSTEM é um dispositivo compacto, de tamanho estável e baixo peso com regulação automática da velocidade (aprox. 1,5m/s). O travão é controlado por forças centrífugas para manter a velocidade constante durante todo o processo de descida. O dispositivo é resistente ao desgaste, ao frio e à corrosão e não causa nenhum desgaste ou dano à corda.

O kit também inclui 2 estropos de resgate pessoal, 1 estropo de ancoragem PES (25 mm) e 1 bolsa de armazenamento


Informação Técnica

TEMPO DE VIDA ÚTIL	10
CARGA MÁXIMA	N/A
INSPEÇÃO	Yearly
RASTREABILIDADE	S/N QR Code
NORMAS	N/A
INTRASTAT	63079098

Imagens do Produto


ESPECIFICAÇÕES

COMPONENTES METÁLICOS	Alumínio, Aço
COMPONENTES TÊXTEIS	Poliéster
OUTROS MATERIAIS	PA, Silicone
TIPO DE FITA	PES Hi-Vis impermeável 44 mm
TIPO DE CORDA	Corda estática PA 10,5 mm
DISPOSITIVO	Dispositivo com regulação automática da velocidade
CONECTORES	1x FS820 ALU fecho de rosca 25kN + 2x ganchos
COMPONENTES	1 x estropo de ancoragem em fita PES - 25 mm ² x estropo de salvamento pessoal 1 x mosquetão ALU1 x sistema de guincho1 x saco de transporte

**PESO POR TAMANHO | EAN
POR TAMANHO**

FS973-10M - 1,80kg - 5605423430714
FS973-100M - 8,50kg - 5605423752335
FS973-105M - 8,80kg - 5605423430479
FS973-1-100M - 1,80kg - 5605423802832
FS973-20M - 2,60kg - 5605423430561
FS973-2-30M - 2,60kg - 5605423437416
FS973-30M - 4,20kg - 5605423430684
FS973-40M - 4,80kg - 5605423821703
FS973-50M - 5,50kg - 5605423800852
FS973-60M - 10,00kg - 5605423430349
FS973-80M - 7,20kg - 5605423752342
FS973-90M - 7,70kg - 5605423430691
FS973-VP-60M - 2,60kg - 5605423805017