



**FS803**

**FILUM - ANCHOR WIRE**

The FALL SAFE® FS803 consists of an 8mm galvanized steel cable, whose ends are joined by a carabiner. Works as a temporary and portable fall arrest system.



**TECHNICAL INFORMATION**

LIFESPAN	UNDEFINED
MAXIMUM LOAD	CE - N/A
INSPECTION	Yearly
TRACEABILITY	S/N
STANDARDS	CE - EN795:2012-B
INTRASTAT	63079098

**PRODUCT PHOTOS**



**SPECIFICATIONS**

MATERIAL	Galvanized steel cable and aluminium
CLASS	B
MAX STRENGTH	22kN
MAX RATED LOAD	120kg
MAX USERS NO.	1
DIMENSIONS	0.50 m to 4 m
WEIGHT PER SIZE   EAN PER SIZE	FS803-0.5M - 0.25kg - 5605423420289
	FS803-4M - 2.00kg - 5605423420234
	FS803-3M - 1.74kg - 5605423420241
	FS803-2M - 1.16kg - 5605423420258
	FS803-2.4M - 0.12kg - 5605423801552
	FS803-1M - 0.58kg - 5605423470345
	FS803-1.5M - 0.75kg - 5605423420272



### FS803

#### FILUM - ANCHOR WIRE

O FALL SAFE® FS803 é constituído por um cabo de aço galvanizado de 8mm, em que as suas extremidades são unidas por um mosquetão. Funciona como sistema ant queda temporário e portátil.



#### Informação Técnica

TEMPO DE VIDA ÚTIL	UNDEFINED
CARGA MÁXIMA	CE - N/A
INSPEÇÃO	Yearly
RASTREABILIDADE	S/N
NORMAS	CE - EN795:2012-B
INTRASTAT	63079098

#### Imagens do Produto



**ESPECIFICAÇÕES**

MATERIAL Galvanized steel cable and aluminium

CLASSE B

FORÇA MÁX 22kN

CARGA MÁXIMA 120kg

Nº MÁX UTILIZADORES 1

DIMENSÕES 0.50 m to 4 m

PESO POR TAMANHO   EAN POR TAMANHO	FS803-0.5M - 0.25kg - 5605423420289
	FS803-4M - 2.00kg - 5605423420234
	FS803-3M - 1.74kg - 5605423420241
	FS803-2M - 1.16kg - 5605423420258
	FS803-2.4M - 0.12kg - 5605423801552
	FS803-1M - 0.58kg - 5605423470345
	FS803-1.5M - 0.75kg - 5605423420272