



PROFESSIONAL

FS504-TB

STRETX - LANYARD WITH ENERGY ABSORBER

FS504 is a simple lanyard (EN354, EN355) made with webbing with internal elastic 40mm which, thanks to its design, reduces the risk of the user tripping due to the length of the rope. The equipment has a SHOXX energy absorber that limits the impact force below 6kN. The lime-colored seams contrast with the black webbing, making it easy to inspect the seams during periodic inspection.



TECHNICAL INFORMATION

LIFESPAN	10
MAXIMUM LOAD	CE - 140Kg
INSPECTION	Yearly
TRACEABILITY	S/N QR Code
STANDARDS	CE - EN354:2010 CE - EN355:2002
INTRASTAT	62113290

PRODUCT PHOTOS



SPECIFICATIONS

MATERIAL	PES, Elastic, ALU, Silicone
WEBBING TYPE	PES tubular webbing with internal elastic 40mm
CONNECTORS	FS33574 ALU twist lock 25kN; FS821 ALU auto lock 23kN (other combinations on request)
MAX LENGTH	2m
ENERGY ABSORBER	Yes, PES - up to 120 Kg
SEAMS PROTECTOR	No
SHARP EDGE TESTED	No
WEIGHT PER SIZE EAN PER SIZE	FS504-TB-2M - 0.52kg - 5605423000665


PROFESSIONAL
FS504-TB
STRETX - LANYARD WITH ENERGY ABSORBER

FS504 é uma longe simples (EN354, EN355) elástica de 40 mm que, graças ao seu design, reduz o risco do utilizador tropeçar devido ao comprimento da corda. O equipamento tem uma absorvedor de energia SHOXX que limita a força de impacto abaixo de 6kN. As costuras cor lima contrastam com a fita preta, facilitando a inspeção das costuras durante a inspeção periódica.


Informação Técnica

TEMPO DE VIDA ÚTIL	10
CARGA MÁXIMA	CE - 140Kg
INSPEÇÃO	Yearly
RASTREABILIDADE	S/N QR Code
NORMAS	CE - EN354:2010 CE - EN355:2002
INTRASTAT	62113290

Imagens do Produto


ESPECIFICAÇÕES

MATERIAL	PES, Elastic, ALU, Silicone
TIPO DE FITA	PES tubular webbing with internal elastic 40mm
CONECTORES	FS33574 ALU twist lock 25kN; FS821 ALU auto lock 23kN (other combinations on request)
COMPRIMENTO MÁX	2m
ABSORBEDOR DE ENERGIA	Yes, PES - up to 120 Kg
PROTETOR DE COSTURAS	No
TESTADO ARESTAS CORTANTES	No
PESO POR TAMANHO EAN POR TAMANHO	FS504-TB-2M - 0.52kg - 5605423000665