

FS861

FIXED BEAM ANCHOR



FALL SAFE® FS861 is a high-strength aluminum alloy removable anchor point with a centrally positioned retainer that prevents beam jamming, with a thickness of 38mm. Fits steel beams.



TECHNICAL INFORMATION

LIFESPAN	UNDEFINED
MAXIMUM LOAD	CE - N/A
INSPECTION	Yearly
TRACEABILITY	S/N
STANDARDS	CE - EN795:2012-B
INTRASTAT	73269098

PRODUCT PHOTOS



SPECIFICATIONS

MATERIAL	Aluminium alloy
CLASS	B
MAX STRENGTH	15kN
MAX USERS NO.	1
WEIGHT PER SIZE EAN/UPC PER SIZE	FS861 - 3,24kg -

FS861

FIXED BEAM ANCHOR



FALL SAFE® FS861 is a high-strength aluminum alloy removable anchor point with a centrally positioned retainer that prevents beam jamming, with a thickness of 38mm. Fits steel beams.



TECHNICAL INFORMATION

LIFESPAN	UNDEFINED
MAXIMUM LOAD	CE - N/A
INSPECTION	Yearly
TRACEABILITY	S/N
STANDARDS	CE - EN795:2012-B
INTRASTAT	73269098

PRODUCT PHOTOS



SPECIFICATIONS

WEIGHT PER SIZE EAN/UPC PER SIZE

FS861 - 3,24kg -

FS861

FIXED BEAM ANCHOR



FALL SAFE® FS861 is a high-strength aluminum alloy removable anchor point with a centrally positioned retainer that prevents beam jamming, with a thickness of 38mm. Fits steel beams.



INFORMATIONS TECHNIQUES

DURÉE DE VIE	UNDEFINED
CHARGE MAXIMALE	CE - N/A
INSPECTION	Yearly
TRAÇABILITÉ	S/N
NORMES	CE - EN795:2012-B
INTRASTAT	73269098

PHOTOS PRODUIT



SPÉCIFICATIONS

WEIGHT PER SIZE EAN/UPC PER SIZE

FS861 - 3,24kg -

FS861

FIXED BEAM ANCHOR



FALL SAFE® FS861 é um ponto de ancoragem removível em liga de alumínio alta resistência com um retentor posicionado centralmente que impede o bloqueio da viga, com uma espessura de 38mm. Adapta-se à vigas de aço.



Informação Técnica

TEMPO DE VIDA ÚTIL	UNDEFINED
CARGA MÁXIMA	CE - N/A
INSPEÇÃO	Yearly
RASTREABILIDADE	S/N
NORMAS	CE - EN795:2012-B
INTRASTAT	73269098

Imagens do Produto



ESPECIFICAÇÕES

MATERIAL	Aluminium alloy
CLASSE	B
FORÇA MÁX	15kN
Nº MÁX UTILIZADORES	1
WEIGHT PER SIZE EAN/UPC PER SIZE	FS861 - 3,24kg -