



PROFESSIONAL

FS600

GRAB-ON ANCHOR LINE

FS600 is an anchor line equipped with 2 aluminum connectors, one to connect to the anchor point on the structure and the other to connect to the chest or back anchor point on full body harnesses, fall protection vests or jumpsuits. fall protection. This equipment has an aluminum rope grab that allows the user to move along the rope safely, thanks to its automatic blocking system. It also has an energy absorber that reduces the impact force to less than 6kN, in case of a fall.



TECHNICAL INFORMATION

LIFESPAN	10
MAXIMUM LOAD	CE - 140kg
INSPECTION	Yearly
TRACEABILITY	S/N QR Code
STANDARDS	CE - EN353-2:2002
INTRASTAT	56090000

PRODUCT PHOTOS



SPECIFICATIONS

MATERIAL	PA, PA6, Aluminium, PES, Silicone
ROPE TYPE	PA (core) + PES (cover) static rope 11mm
DEVICE	ALU rope grab
CONNECTORS	2 x FS820 ALU screw lock 25kN (other combinations on request)
MAX LENGTH	140 m
ENERGY ABSORBER	Yes
SEAMS PROTECTOR	Yes
SHARP EDGE TESTED	No
MAX RATED LOAD	140 kg
DIMENSIONS	110x55x31,5 mm / Ø20 mm

WEIGHT PER SIZE EAN/UPC PER SIZE

FS600-2M - 0,20kg - 5605423801514
FS600-80M - 5,50kg - 5605423320879
FS600-75M - 5,00kg - 5605423321531
FS600-70M - 4,50kg - 5605423321524
FS600-65M - 4,00kg - 5605423320862
FS600-60M - 3,50kg - 5605423320077
FS600-5M - 0,35kg - 5605423320008
FS600-50M - 3,00kg - 5605423320060
FS600-40M - 2,50kg - 5605423320886
FS600-35M - 2,00kg - 5605423349894
FS600-30M - 1,50kg - 5605423320053
FS600-25M - 1,00kg - 5605423320046
FS600-20M - 0,80kg - 5605423320039
FS600-15M - 0,50kg - 5605423320022
FS600-140M - 9,00kg - 5605423321548
FS600-10M - 0,45kg - 5605423320015
FS600-100M - 6,40kg - 5605423320404



PROFESSIONAL

FS600

GRAB-ON ANCHOR LINE

FS600 is an anchor line equipped with 2 aluminum connectors, one to connect to the anchor point on the structure and the other to connect to the chest or back anchor point on full body harnesses, fall protection vests or jumpsuits. fall protection. This equipment has an aluminum rope grab that allows the user to move along the rope safely, thanks to its automatic blocking system. It also has an energy absorber that reduces the impact force to less than 6kN, in case of a fall.



INFORMATIONS TECHNIQUES

DURÉE DE VIE	10
CHARGE MAXIMALE	CE - 140kg
INSPECTION	Yearly
TRAÇABILITÉ	S/N QR Code
NORMES	CE - EN353-2:2002
INTRASTAT	56090000

PHOTOS PRODUIT



SPÉCIFICATIONS

WEIGHT PER SIZE EAN/UPC PER SIZE

FS600-2M	- 0,20kg	- 5605423801514
FS600-80M	- 5,50kg	- 5605423320879
FS600-75M	- 5,00kg	- 5605423321531
FS600-70M	- 4,50kg	- 5605423321524
FS600-65M	- 4,00kg	- 5605423320862
FS600-60M	- 3,50kg	- 5605423320077
FS600-5M	- 0,35kg	- 5605423320008
FS600-50M	- 3,00kg	- 5605423320060
FS600-40M	- 2,50kg	- 5605423320886
FS600-35M	- 2,00kg	- 5605423349894
FS600-30M	- 1,50kg	- 5605423320053
FS600-25M	- 1,00kg	- 5605423320046
FS600-20M	- 0,80kg	- 5605423320039
FS600-15M	- 0,50kg	- 5605423320022
FS600-140M	- 9,00kg	- 5605423321548
FS600-10M	- 0,45kg	- 5605423320015
FS600-100M	- 6,40kg	- 5605423320404



PROFESSIONAL

FS600

GRAB-ON ANCHOR LINE

FS600 é uma linha de ancoragem equipada com 2 conectores em alumínio (EN362), um para se conectar ao ponto de ancoragem na estrutura e outro para se conectar ao ponto de ancoragem no peito ou dorsal em arneses de corpo inteiro, coletes de proteção contra queda ou macacão de proteção contra queda. Este equipamento tem um bloqueador de corda, em alumínio que permite ao utilizador deslocar-se ao longo da corda de forma segura, graças ao seu sistema de bloqueio automático. Possui ainda um absorbedor de energia que reduz a força de impacto para menos de 6kN, no caso de queda.



Informação Técnica

TEMPO DE VIDA ÚTIL	10
CARGA MÁXIMA	CE - 140kg
INSPEÇÃO	Yearly
RASTREABILIDADE	S/N QR Code
NORMAS	CE - EN353-2:2002
INTRASTAT	56090000

Imagens do Produto



ESPECIFICAÇÕES

MATERIAL	PA, PA6, Alumínio, PES, Silicone
TIPO DE CORDA	PA (interior) + PES (exterior) corda estática 11mm
DISPOSITIVO	ALU bloqueador de corda
CONECTORES	2 x FS820 ALU fecho de rosca 25kN (outras combinações a pedido)
COMPRIMENTO MÁX	140 m
ABSORBEDOR DE ENERGIA	Sim
PROTETOR DE COSTURAS	Sim
TESTADO ARESTAS CORTANTES	Não
CARGA MÁXIMA	140 kg
DIMENSÕES	110x55x31,5 mm / Ø20 mm

WEIGHT PER SIZE EAN/UPC PER SIZE

FS600-2M - 0,20kg - 5605423801514
FS600-80M - 5,50kg - 5605423320879
FS600-75M - 5,00kg - 5605423321531
FS600-70M - 4,50kg - 5605423321524
FS600-65M - 4,00kg - 5605423320862
FS600-60M - 3,50kg - 5605423320077
FS600-5M - 0,35kg - 5605423320008
FS600-50M - 3,00kg - 5605423320060
FS600-40M - 2,50kg - 5605423320886
FS600-35M - 2,00kg - 5605423349894
FS600-30M - 1,50kg - 5605423320053
FS600-25M - 1,00kg - 5605423320046
FS600-20M - 0,80kg - 5605423320039
FS600-15M - 0,50kg - 5605423320022
FS600-140M - 9,00kg - 5605423321548
FS600-10M - 0,45kg - 5605423320015
FS600-100M - 6,40kg - 5605423320404