



BASIC

FS550-HN

CHIMANGO 5 DOUBLE LANYARD WITH ENERGY ABSORBER

FALL SAFE® FS550 - CHIMANGO 5 - DOUBLE is a double 11mm polyamide rope lanyard and an energy absorber package that limits the impact force below 6kN, in the event of a fall.

The FS550 physically links the user to the structure of the job site and prevents the user from free-falling.



TECHNICAL INFORMATION

LIFESPAN	10
MAXIMUM LOAD	CE - 140kg
INSPECTION	Yearly
TRACEABILITY	S/N QR Code
STANDARDS	CE - EN354:2010 CE - EN355:2002
INTRASTAT	56090000

PRODUCT PHOTOS



SPECIFICATIONS

MATERIAL	PES and ALU
ROPE TYPE	PES (core) + PES (cover) static rope - Ø 11 mm
CONNECTORS	FS33500-2L auto twist-lock 30kN; FS843 auto lock 25kN (other combinations on request)
MAX LENGTH	2m
ENERGY ABSORBER	Yes
SEAMS PROTECTOR	Yes
SHARP EDGE TESTED	No
WEIGHT PER SIZE EAN/UPC PER SIZE	FS550-HN-1M - 1.00kg - 5605423752823 FS550-HN-1.5M - 1.20kg - 5605423752779 FS550-HN-2M - 1.40kg - 5605423809138



BASIC

FS550-HN

CHIMANGO 5 DOUBLE LANYARD WITH ENERGY ABSORBER

FALL SAFE® FS550 - CHIMANGO 5 - DOUBLE is a double 11mm polyamide rope lanyard and an energy absorber package that limits the impact force below 6kN, in the event of a fall. The FS550 physically links the user to the structure of the job site and prevents the user from free-falling.



INFORMATIONS TECHNIQUES

DURÉE DE VIE	10
CHARGE MAXIMALE	CE - 140kg
INSPECTION	Yearly
TRAÇABILITÉ	S/N QR Code
NORMES	CE - EN354:2010 CE - EN355:2002
INTRASTAT	56090000

PHOTOS PRODUIT



SPÉCIFICATIONS

WEIGHT PER SIZE EAN/UPC PER SIZE	FS550-HN-1M - 1.00kg - 5605423752823
	FS550-HN-1.5M - 1.20kg - 5605423752779
	FS550-HN-2M - 1.40kg - 5605423809138



BASIC

FS550-HN

CHIMANGO 5 DOUBLE LANYARD WITH ENERGY ABSORBER

FALL SAFE® FS550 - CHIMANGO 5 - DOUBLE é uma longa dupla em corda de poliamida de 11mm e um pacote de absorvedor de energia que limita a força de impacto abaixo de 6kN, em caso de queda.
O FS550 liga fisicamente o usuário à estrutura do local de trabalho e impede a queda livre do utilizador.



Informação Técnica

TEMPO DE VIDA ÚTIL	10
CARGA MÁXIMA	CE - 140kg
INSPEÇÃO	Yearly
RASTREABILIDADE	S/N QR Code
NORMAS	CE - EN354:2010 CE - EN355:2002
INTRASTAT	56090000

Imagens do Produto



ESPECIFICAÇÕES

MATERIAL	PES and ALU
TIPO DE CORDA	PES (core) + PES (cover) static rope - Ø 11 mm
CONECTORES	FS33500-2L auto twist-lock 30kN; FS843 auto lock 25kN (other combinations on request)
COMPRIMENTO MÁX	2m
ABSORBEDOR DE ENERGIA	Yes
PROTETOR DE COSTURAS	Yes
TESTADO ARESTAS CORTANTES	No
WEIGHT PER SIZE EAN/UPC PER SIZE	FS550-HN-1M - 1.00kg - 5605423752823 FS550-HN-1.5M - 1.20kg - 5605423752779 FS550-HN-2M - 1.40kg - 5605423809138