



BASIC

FS038A-TC

JYNX 5A - DOUBLE LANYARD WEBBING WITH ADJUSTER

FS038A – JYNX 5A - DOUBLE LANYARD WEBBING WITH ADJUSTER it's a double lanyard composed by 27x3mm polyester webbing, polyester heavy duty stitches and an aluminium adjuster.

| TECHNICAL INFORMATION | |
|-----------------------|-----------------|
| LIFESPAN | 10 |
| MAXIMUM LOAD | CE - 120kg |
| INSPECTION | Yearly |
| TRACEABILITY | S/N QR Code |
| STANDARDS | CE - EN354:2010 |
| INTRASTAT | 56090000 |

PRODUCT PHOTOS



SPECIFICATIONS

| | |
|--------------------------------|--|
| MATERIAL | PES and ALU |
| WEBBING TYPE | PES webbing 27 mm x 3 mm |
| CONNECTORS | FS33547 auto twist-lock 25kN; FS33562 auto lock 25kN (other combinations on request) |
| MAX LENGTH | 2m |
| ENERGY ABSORBER | No |
| SEAMS PROTECTOR | Yes |
| SHARP EDGE TESTED | No |
| WEIGHT PER SIZE EAN PER SIZE | FS038A-TC-2M - 1.26kg - 5605423808346 |



BASIC

FS038A-TC

JYNX 5A - DOUBLE LANYARD WEBBING WITH ADJUSTER

FS038A – JYNX 5A - CORDA DUPLA COM AJUSTADOR é uma corda dupla composta por fita de poliéster 27x3mm, pespontos de poliéster e ajustador de alumínio.

Informação Técnica

| | |
|--------------------|-----------------|
| TEMPO DE VIDA ÚTIL | 10 |
| CARGA MÁXIMA | CE - 120kg |
| INSPEÇÃO | Yearly |
| RASTREABILIDADE | S/N QR Code |
| NORMAS | CE - EN354:2010 |
| INTRASTAT | 56090000 |

Imagens do Produto



ESPECIFICAÇÕES

| | |
|------------------------------------|--|
| MATERIAL | PES and ALU |
| TIPO DE FITA | PES webbing 27 mm x 3 mm |
| CONECTORES | FS33547 auto twist-lock 25kN; FS33562 auto lock 25kN (other combinations on request) |
| COMPRIMENTO MÁX | 2m |
| ABSORBEDOR DE ENERGIA | No |
| PROTETOR DE COSTURAS | Yes |
| TESTADO ARESTAS CORTANTES | No |
| PESO POR TAMANHO EAN POR TAMANHO | FS038A-TC-2M - 1.26kg - 5605423808346 |