



PROFESSIONAL

FS222EVO

ULTRA EVO HARNESS

ULTRA EVO FS222EVO is a specifically designed to work at height harness, produced according to EN358 and EN361 – maximum load up to 140kg. It is equipped with 2 Side D-Rings for work positioning, 2 front loops for fall arrest, 1 back attachment aluminium ring ("A") ergonomic support belt, ergonomic backpad, padded legs, lanyard keepers, 6 point size adjustment for perfect fit and a reflective fabric to keep you visible and safer. The airflow through all the harness layers is assured by the new and improved Croc padding. It is identified with an RFID tag, S/N label and QR code for easy tracking and control.

TECHNICAL INFORMATION

| | |
|--------------|------------------------------------|
| LIFESPAN | 10 |
| MAXIMUM LOAD | CE - 140kg |
| INSPECTION | Yearly |
| TRACEABILITY | S/N RFID QR Code |
| STANDARDS | CE - EN361:2002 CE - EN358:2018 |
| INTRASTAT | 63079098 |

PRODUCT PHOTOS



SPECIFICATIONS

| | |
|--------------------------------|--|
| METAL PARTS | Aluminium, steel |
| TEXTILE PARTS | Polyester |
| OTHER COMPONENTS MATERIAL | PA6, silicone |
| WEBBING TYPE | PES 45mm water-repellent |
| D-RINGS | ALU 45° D-Ring back and sides, ergonomic loops front |
| ANCHOR POINTS (A) | 4 |
| SHOULDER PADDING | Yes - Croc Smooth Padding 3.0 |
| LUMBAR PADDING | Yes - Croc Smooth Padding 3.0 |
| LEG PADDING | Yes |
| PADDING MATERIAL | TPU, EVA, PA, high visibility mesh and fabric PES |
| SEAT CONNECTION POINT | No |
| TOOL HOLDERS | No |
| ADJUSTMENT POINTS | 5 |
| BUCKLES | 4 ALU IZY quick connect buckles; 2 ST 3-bar buckles |
| FALL ARREST INDICATORS | Yes |
| LANYARD KEEPERS | Yes |
| WEIGHT PER SIZE EAN PER SIZE | FS222EVO-S/M - 1,70kg - 5605423810059 FS222EVO-L/XL - 1,90kg - 5605423810066 FS222EVO-XXL - 1,90kg - 5605423810073 |



PROFESSIONAL

FS222EVO

ULTRA EVO HARNESS

O ULTRA EVO FS222EVO é um arnês especificamente concebido para trabalhar em altura, produzido de acordo com a EN358 e EN361 – carga máxima até 140kg. É equipado com 2 anéis D laterais para posicionamento no trabalho, 2 loops frontais, 1 anel de alumínio nas costas ("A"), cinto para suporte ergonómico, pernas acolchoadas, suportes de longes, ajuste de tamanho com 6 pontos para ajuste perfeito e um tecido refletor para manter o utilizador visível e mais seguro. O fluxo de ar através de todas as camadas do arnês é assegurado pelo novo e melhorado padding Croc 3.0. É identificado com uma etiqueta RFID, etiqueta S/N e código QR para fácil rastreabilidade e controlo.

Informação Técnica

| | |
|--------------------|------------------------------------|
| TEMPO DE VIDA ÚTIL | 10 |
| CARGA MÁXIMA | CE - 140kg |
| INSPEÇÃO | Yearly |
| RASTREABILIDADE | S/N RFID QR Code |
| NORMAS | CE - EN361:2002 CE - EN358:2018 |
| INTRASTAT | 63079098 |

Imagens do Produto



ESPECIFICAÇÕES

| | |
|------------------------------------|--|
| COMPONENTES METÁLICOS | Aluminium, steel |
| COMPONENTES TÊXTEIS | Polyester |
| OUTROS MATERIAIS | PA6, silicone |
| TIPO DE FITA | PES 45mm water-repellent |
| D-RINGS | ALU 45° D-Ring back and sides, ergonomic loops front |
| PONTOS DE ANCORAGEM (A) | 4 |
| PADDING OMBROS | Yes - Croc Smooth Padding 3.0 |
| PADDING LOMBAR | Yes - Croc Smooth Padding 3.0 |
| PADDING PERNA | Yes |
| MATERIAL DO PADDING | TPU, EVA, PA, high visibility mesh and fabric PES |
| PONTO LIGAÇÃO DE CADEIRA | No |
| SUPORTE DE FERRAMENTAS | No |
| PONTOS DE AJUSTE | 5 |
| FIVELAS | 4 ALU IZY quick connect buckles; 2 ST 3-bar buckles |
| INDICADORES DE QUEDA | Yes |
| SUPORTE DE LONGES | Yes |
| PESO POR TAMANHO EAN POR TAMANHO | FS222EVO-S/M - 1,70kg - 5605423810059 FS222EVO-L/XL - 1,90kg - 5605423810066 FS222EVO-XXL - 1,90kg - 5605423810073 |