



PROFESSIONAL

FS222EVO

ULTRA EVO HARNESS

ULTRA EVO FS222EVO is a specifically designed to work at height harness, produced according to EN358 and EN361 – maximum load up to 140kg. It is equipped with 2 Side D-Rings for work positioning, 2 front loops for fall arrest, 1 back attachment aluminium ring ("A") ergonomic support belt, ergonomic backpad, padded legs, lanyard keepers, 6 point size adjustment for perfect fit and a reflective fabric to keep you visible and safer. The airflow through all the harness layers is assured by the new and improved Croc padding. It is identified with an RFID tag, S/N label and QR code for easy tracking and control.

TECHNICAL INFORMATION

LIFESPAN	10
MAXIMUM LOAD	CE - 140kg
INSPECTION	Yearly
TRACEABILITY	S/N RFID QR Code
STANDARDS	CE - EN361:2002 CE - EN358:2018
INTRASTAT	63079098

PRODUCT PHOTOS



SPECIFICATIONS

METAL PARTS	Aluminium, steel
TEXTILE PARTS	Polyester
OTHER COMPONENTS MATERIAL	PA6, silicone
WEBBING TYPE	PES 45mm water-repellent
D-RINGS	ALU 45° D-Ring back and sides, ergonomic loops front
ANCHOR POINTS (A)	4
SHOULDER PADDING	Yes - Croc Smooth Padding 3.0
LUMBAR PADDING	Yes - Croc Smooth Padding 3.0
LEG PADDING	Yes
PADDING MATERIAL	TPU, EVA, PA, high visibility mesh and fabric PES
SEAT CONNECTION POINT	No
TOOL HOLDERS	No
ADJUSTMENT POINTS	5
BUCKLES	4 ALU IZY quick connect buckles; 2 ST 3-bar buckles
FALL ARREST INDICATORS	Yes
LANYARD KEEPERS	Yes
WEIGHT PER SIZE EAN PER SIZE	FS222EVO-S/M - 1.70kg - 5605423810059 FS222EVO-XXL - 2.00kg - 5605423810073 FS222EVO-L/XL - 1.90kg - 5605423810066



PROFESSIONAL

FS222EVO

ULTRA EVO HARNESS

O ULTRA EVO FS222EVO é um arnês especificamente concebido para trabalhar em altura, produzido de acordo com a EN358 e EN361 – carga máxima até 140kg. É equipado com 2 anéis D laterais para posicionamento no trabalho, 2 loops frontais, 1 anel de alumínio nas costas ("A"), cinto para suporte ergonómico, pernas acolchoadas, suportes de longes, ajuste de tamanho com 6 pontos para ajuste perfeito e um tecido refletor para manter o utilizador visível e mais seguro. O fluxo de ar através de todas as camadas do arnês é assegurado pelo novo e melhorado padding Croc 3.0. É identificado com uma etiqueta RFID, etiqueta S/N e código QR para fácil rastreabilidade e controlo.

Informação Técnica

TEMPO DE VIDA ÚTIL	10
CARGA MÁXIMA	CE - 140kg
INSPEÇÃO	Yearly
RASTREABILIDADE	S/N RFID QR Code
NORMAS	CE - EN361:2002 CE - EN358:2018
INTRASTAT	63079098

Imagens do Produto



ESPECIFICAÇÕES

COMPONENTES METÁLICOS	Aluminium, steel
COMPONENTES TÊXTEIS	Polyester
OUTROS MATERIAIS	PA6, silicone
TIPO DE FITA	PES 45mm water-repellent
D-RINGS	ALU 45° D-Ring back and sides, ergonomic loops front
PONTOS DE ANCORAGEM (A)	4
PADDING OMBROS	Yes - Croc Smooth Padding 3.0
PADDING LOMBAR	Yes - Croc Smooth Padding 3.0
PADDING PERNA	Yes
MATERIAL DO PADDING	TPU, EVA, PA, high visibility mesh and fabric PES
PONTO LIGAÇÃO DE CADEIRA	No
SUPORTE DE FERRAMENTAS	No
PONTOS DE AJUSTE	5
FIVELAS	4 ALU IZY quick connect buckles; 2 ST 3-bar buckles
INDICADORES DE QUEDA	Yes
SUPORTE DE LONGES	Yes
PESO POR TAMANHO EAN POR TAMANHO	FS222EVO-S/M - 1.70kg - 5605423810059 FS222EVO-XXL - 2.00kg - 5605423810073 FS222EVO-L/XL - 1.90kg - 5605423810066