



PROFESSIONAL

FS512

STERTX EVO - DOUBLE LANYARD WITH ENERGY ABSORBER - EUROPEAN VERSION

FS512 - STERTX EVO is a double lanyard (EN354, EN355) that physically links the user to the workplace structure and arrests the free fall in case of it. This lanyard is made with 25mm polyester webbing, a PES 45mm energy absorber and PES heavy duty seams. It supports a maximum load of 140 kg. The lime colored seams contrast with the black webbing making it easier to inspect the seams during periodic inspection. The design of this equipment, with the retractable webbing, at rest, makes the webbing shorter and does not get in the way of the user.



TECHNICAL INFORMATION

LIFESPAN	10
MAXIMUM LOAD	CE - 140kg
INSPECTION	Yearly
TRACEABILITY	S/N QR Code
STANDARDS	CE - EN354:2010 CE - EN355:2002
INTRASTAT	56090000

PRODUCT PHOTOS



SPECIFICATIONS

MATERIAL	PES, ALU, Silicone
WEBBING TYPE	PES retractable tubular webbing 25mm
CONNECTORS	FS33574 ALU twist lock 25kN; FS821 ALU auto lock 23kN (other combinations on request)
MAX LENGTH	1.80 m
ENERGY ABSORBER	Yes, PES - up to 120 Kg
SEAMS PROTECTOR	No
SHARP EDGE TESTED	No
WEIGHT PER SIZE EAN/UPC PER SIZE	FS512-TB-1.8M - 1.10kg - 5605423809916 FS512-FB-1.8M - 1.40kg - 5605423814941 FS512-CB-1.8M - 1.10kg - 5605423809909



PROFESSIONAL

FS512

STERTX EVO - DOUBLE LANYARD WITH ENERGY ABSORBER - EUROPEAN VERSION

FS512 - STERTX EVO is a double lanyard (EN354, EN355) that physically links the user to the workplace structure and arrests the free fall in case of it. This lanyard is made with 25mm polyester webbing, a PES 45mm energy absorber and PES heavy duty seams. It supports a maximum load of 140 kg. The lime colored seams contrast with the black webbing making it easier to inspect the seams during periodic inspection. The design of this equipment, with the retractable webbing, at rest, makes the webbing shorter and does not get in the way of the user.



INFORMATIONS TECHNIQUES

DURÉE DE VIE	10
CHARGE MAXIMALE	CE - 140kg
INSPECTION	Yearly
TRAÇABILITÉ	S/N QR Code
NORMES	CE - EN354:2010 CE - EN355:2002
INTRASTAT	56090000

PHOTOS PRODUIT



SPÉCIFICATIONS

WEIGHT PER SIZE EAN/UPC PER SIZE	FS512-TB-1.8M - 1.10kg - 5605423809916
	FS512-FB-1.8M - 1.40kg - 5605423814941
	FS512-CB-1.8M - 1.10kg - 5605423809909



PROFESSIONAL

FS512

STERTX EVO - DOUBLE LANYARD WITH ENERGY ABSORBER - EUROPEAN VERSION

FS512 - STERTX EVO é uma longa dupla (EN354, EN355) que liga fisicamente o utilizador à estrutura do local de trabalho e impede a queda livre em caso de queda. Esta longa é feita com tecido de poliéster de 25 mm, um absorvedor de energia PES de 45 mm e costuras de PES. Suporta uma carga máxima de 140 kg. As costuras cor lima contrastam com a fita preta, facilitando a inspeção das costuras durante a inspeção periódica. O design deste equipamento, com a fita retrátil, em repouso, torna a fita mais curta e não atrapalha o utilizador.



Informação Técnica

TEMPO DE VIDA ÚTIL	10
CARGA MÁXIMA	CE - 140kg
INSPEÇÃO	Yearly
RASTREABILIDADE	S/N QR Code
NORMAS	CE - EN354:2010 CE - EN355:2002
INTRASTAT	56090000

Imagens do Produto



ESPECIFICAÇÕES

MATERIAL	PES, ALU, Silicone
TIPO DE FITA	PES retractable tubular webbing 25mm
CONECTORES	FS33574 ALU twist lock 25kN; FS821 ALU auto lock 23kN (other combinations on request)
COMPRIMENTO MÁX	1.80 m
ABSORBEDOR DE ENERGIA	Yes, PES - up to 120 Kg
PROTETOR DE COSTURAS	No
TESTADO ARESTAS CORTANTES	No
WEIGHT PER SIZE EAN/UPC PER SIZE	FS512-TB-1.8M - 1.10kg - 5605423809916 FS512-FB-1.8M - 1.40kg - 5605423814941 FS512-CB-1.8M - 1.10kg - 5605423809909