



PROFESSIONAL

FS224

SCAFFOLDER - HARNESS

FS224 SCAFFOLDER HARNESS, with an ergonomic back and leg pads that move along the user, IZY quick connect aluminium buckles, including a dorsal D-ring and a frontal D-ring, was designed for scaffolding workers. The airflow through all the harness layers is assured by the new and improved Croc padding. This innovation also allows for a lighter and more ergonomic final product, that is extremely comfortable for use for several hours.

With reflective and extra breathable fabric, the FS224 combines the lightness of its composition with the FALL SAFE® quality assurance.



TECHNICAL INFORMATION

LIFESPAN	10
MAXIMUM LOAD	CE - 140kg
INSPECTION	N/A
TRACEABILITY	N/A
STANDARDS	CE - EN361:2002
INTRASTAT	63079098

PRODUCT PHOTOS



SPECIFICATIONS

METAL PARTS	Aluminium
TEXTILE PARTS	PES
OTHER COMPONENTS MATERIAL	PA6, Silicone
WEBBING TYPE	PES 45mm water-repellent
D-RINGS	Aluminium D-Rings back and front
ANCHOR POINTS (A)	2
SHOULDER PADDING	Yes - Croc Smooth Padding 3.0
LUMBAR PADDING	No
TOOL HOLDERS	4
TOOL HOLDERS MAX LOAD	15kg
ADJUSTMENT POINTS	4
BUCKLES	IZY Quick connect
FALL ARREST INDICATORS	Yes
LANYARD KEEPERS	Yes
MAX RATED LOAD	140kg
WEIGHT PER SIZE EAN PER SIZE	FS224-S/M - 2,12kg - 5605423570120 FS224-XXL - 2,17kg - 5605423570144 FS224-L/XL - 0,00kg - 5605423570137


PROFESSIONAL
FS224
SCAFFOLDER - HARNESS

FS224, com costas ergonómicas e almofadadas, com pernas que se movem ao longo do utilizador, fivelas de alumínio de conexão rápida IZY, incluindo uma argola em D dorsal e uma argola em D frontal, foi projetado para trabalhadores e trabalhos em andaimes.

O fluxo de ar através de todas as camadas do arnês é garantido pelo novo e melhorado acolchoamento Croc. Esta inovação também permite um produto final mais leve e ergonómico, extremamente confortável para uso por várias horas.

Com tecido refletivo e extra respirável, o FS224 combina a leveza de sua composição com a garantia de qualidade FALL SAFE®.


Informação Técnica

TEMPO DE VIDA ÚTIL	10
CARGA MÁXIMA	CE - 140kg
INSPEÇÃO	N/A
RASTREABILIDADE	N/A
NORMAS	CE - EN361:2002
INTRASTAT	63079098

Imagens do Produto


ESPECIFICAÇÕES

COMPONENTES METÁLICOS	Aluminium
COMPONENTES TÊXTEIS	PES
OUTROS MATERIAIS	PA6, Silicone
TIPO DE FITA	PES 45mm water-repellent
D-RINGS	Aluminium D-Rings back and front
PONTOS DE ANCORAGEM (A)	2
PADDING OMBROS	Yes - Croc Smooth Padding 3.0
PADDING LOMBAR	No
SUORTE DE FERRAMENTAS	4
CAPACIDADE MÁX. DO SUORTE DE FERRAMENTAS	15kg
PONTOS DE AJUSTE	4
FIVELAS	IZY Quick connect
INDICADORES DE QUEDA	Yes
SUORTE DE LONGES	Tes
CARGA MÁXIMA	140kg
PESO POR TAMANHO EAN POR TAMANHO	FS224-S/M - 2,12kg - 5605423570120 FS224-XXL - 2,17kg - 5605423570144 FS224-L/XL - 0,00kg - 5605423570137