



PROFESSIONAL

FS932

RETRACTABLE FALL ARRESTER BLOCK WEBBING - 7M

SEVEN M is an extremely lightweight fall arrest retractable block made of carbon and stainless steel. Dyneema® webbing makes it abrasion resistant and more durable. It is extra resistant thanks to the materials and design of the casing. FS932 is 7 meters long and has fall indicators for greater user safety. Its lightness makes it excellent for construction work, scaffolding and roof works.



TECHNICAL INFORMATION

LIFESPAN	UNDEFINED
MAXIMUM LOAD	CE - 100kg
INSPECTION	Yearly
TRACEABILITY	S/N QR Code
STANDARDS	CE - EN360:2002
INTRASTAT	84798997

PRODUCT PHOTOS



SPECIFICATIONS

MATERIAL	Steel, PA6, Dyneema®
WEBBING TYPE	Dyneema®
FALL ARREST INDICATORS	Yes
CONNECTORS	Steel
ENERGY ABSORBER	No
SHARP EDGE TESTED	No
MAX USERS NO.	1
HOUSING	PA6 + Glass filled
CHASSIS	Stainless steel, carbon steel
LENGTH	7 m
WEIGHT PER SIZE EAN/UPC PER SIZE	FS932 - 2.10kg - 5605423800609



PROFESSIONAL

FS932

RETRACTABLE FALL ARRESTER BLOCK WEBBING - 7M

SEVEN M is an extremely lightweight fall arrest retractable block made of carbon and stainless steel. Dyneema® webbing makes it abrasion resistant and more durable. It is extra resistant thanks to the materials and design of the casing. FS932 is 7 meters long and has fall indicators for greater user safety. Its lightness makes it excellent for construction work, scaffolding and roof works.



INFORMATIONS TECHNIQUES

DURÉE DE VIE	UNDEFINED
CHARGE MAXIMALE	CE - 100kg
INSPECTION	Yearly
TRAÇABILITÉ	S/N QR Code
NORMES	CE - EN360:2002
INTRASTAT	84798997

PHOTOS PRODUIT



SPÉCIFICATIONS

WEIGHT PER SIZE EAN/UPC PER SIZE

FS932 - 2.10kg - 5605423800609



PROFESSIONAL

FS932

RETRACTABLE FALL ARRESTER BLOCK WEBBING - 7M

SEVEN M é um bloco retrátil extremamente leve fabricado em aço carbono e inoxidável. A fita Dyneema® torna-o resistente à abrasão e mais durável. É extra resistente graças aos materiais e design do invólucro. FS932 tem 7 metros de comprimento e indicadores de queda para maior segurança do utilizador. A sua leveza torna-o excelente para trabalhos em construção, andaimes e telhados.



Informação Técnica

TEMPO DE VIDA ÚTIL	UNDEFINED
CARGA MÁXIMA	CE - 100kg
INSPEÇÃO	Yearly
RASTREABILIDADE	S/N QR Code
NORMAS	CE - EN360:2002
INTRASTAT	84798997

Imagens do Produto



ESPECIFICAÇÕES

MATERIAL	Steel, PA6, Dyneema®
TIPO DE FITA	Dyneema®
INDICADORES DE QUEDA	Yes
CONECTORES	Steel
ABSORBEDOR DE ENERGIA	No
TESTADO ARESTAS CORTANTES	No
CARGA MÁXIMA	100kg
Nº MÁX UTILIZADORES	1
INVÓLUCRO	PA6 + Glass filled
CHASSIS	Stainless steel, carbon steel
COMPRIMENTO	7 m
WEIGHT PER SIZE EAN/UPC PER SIZE	FS932 - 2.10kg - 5605423800609