



**PROFESSIONAL**

**FS33381**

**LORY SAFE DESCENDER**

LORY SAFE is a self-braking descender for single rope use with unimpeded movement of the cam (for industrial use) and is certified according to the norms: EN 341:2011 Class A, EN 12841:2006 Type C, EN 795:2012 Type B.

- Robust multipurpose device for use in industrial access and sport climbing applications;
- Its functionality spans the range from rope access and rescue descender device through semi-automatic belay device and in combination with Lanyard WP also temporary anchoring.



TECHNICAL INFORMATION	
LIFESPAN	UNDEFINED
MAXIMUM LOAD	CE - 180kg
INSPECTION	Yearly
TRACEABILITY	S/N
STANDARDS	CE - EN341:2011-2A CE - EN12841:2006-C CE - EN795:2012
INTRASTAT	84799070

**PRODUCT PHOTOS**



**SPECIFICATIONS**

MATERIAL	Aluminium
ROPE TYPE	EN 1891-A Ø11mm (EN341) Ø10mm-12mm (EN 12841) Low-stretch, Ø = 11 mm(ANSI/ASSE Z359.4-2013)
DEVICE	Single rope descender with two jamming positions and anchoring device
MAX RATED LOAD	EN341 - 30-180kg (maximum descent 190m, approved for 22 consecutive descents) EN12841 - 225kg ANSI/ASSE Z359.4-2013 - single person 130 lb to 310 lb, 59 kg to 141 kg
DIMENSIONS	71x125mm
WEIGHT PER SIZE   EAN PER SIZE	FS33381 - 0.23kg - 5605423800395



**PROFESSIONAL**

**FS33381**

**LORY SAFE DESCENDER**

LORY SAFE é um descensor autobloqueante para uso em corda única com movimento desimpedido da câmara (para uso industrial) e é certificado de acordo com as normas: EN 341:2011 Classe A, EN 12841:2006 Tipo C, EN 795:2012 Tipo B.

- Dispositivo multiuso robusto para uso em aplicações de acesso industrial e escalada desportiva;
- A sua funcionalidade abrange desde acesso por corda e dispositivo de descida de resgate até dispositivo de segurança semiautomático e em combinação com Lanyard WP também ancoragem temporária.



Informação Técnica	
TEMPO DE VIDA ÚTIL	UNDEFINED
CARGA MÁXIMA	CE - 180kg
INSPEÇÃO	Yearly
RASTREABILIDADE	S/N
NORMAS	CE - EN341:2011-2A CE - EN12841:2006-C CE - EN795:2012
INTRASTAT	84799070

**Imagens do Produto**



**ESPECIFICAÇÕES**

MATERIAL	Aluminium
TIPO DE CORDA	EN 1891-A Ø11mm (EN341) Ø10mm-12mm (EN 12841) Low-stretch, Ø = 11 mm(ANSI/ASSE Z359.4-2013)
DISPOSITIVO	Single rope descender with two jamming positions and anchoring device
CARGA MÁXIMA	EN341 - 30-180kg (maximum descent 190m, approved for 22 consecutive descents) EN12841 - 225kg ANSI/ASSE Z359.4-2013 - single person 130 lb to 310 lb, 59 kg to 141 kg
DIMENSÕES	71x125mm
PESO POR TAMANHO   EAN POR TAMANHO	FS33381 - 0.23kg - 5605423800395