

**PROFESSIONAL**



**FS267**

**DOUGLAS PRO - ARBORIST HARNESS**

DOUGLAS PRO is a harness specifically designed for arborism and work positioning. It is conforming EN813 and EN358 and it is equipped with a floating bridge, which is essential to the lateral movement achievable within restricted areas. It has an anchor plate to enable users to have 3 sitting positions for different environment needs. Integrated rated tool loops and chain saw attachment at back. Integral side buckles for bridged adjustment and optimizes comfort and correct positioning. Has a special Croc padding with air flow system for extra comfort and stationary rope techniques work.



**TECHNICAL INFORMATION**

LIFESPAN	10
MAXIMUM LOAD	CE - 140kg
INSPECTION	Yearly
TRACEABILITY	S/N RFID QR Code
STANDARDS	CE - EN358:2018 CE - EN813:2008
INTRASTAT	63079098

**PRODUCT PHOTOS**



**SPECIFICATIONS**

METAL PARTS	Aluminium, steel
TEXTILE PARTS	Polyester, static rope
OTHER COMPONENTS MATERIAL	Elastic (webbing keeper)
WEBBING TYPE	PES 30mm with high-abrasion resistance
D-RINGS	ALU d-ring at sides
ANCHOR POINTS (A)	2
LUMBAR PADDING	Yes - Croc Extra Hard Padding 3.0
LEG PADDING	Yes - Semi rigid wide leg pad
SEAT CONNECTION POINT	No
TOOL HOLDERS	10 + reinforced point at back for chainsaw
ADJUSTMENT POINTS	7
BUCKLES	3 ALU quick connect buckles; 2 ST bar buckles
FALL ARREST INDICATORS	No
WEIGHT PER SIZE   EAN PER SIZE	FS267-S/M - 2.40kg - 5605423803655 FS267-XXL - 3.00kg - 5605423803662 FS267-L/XL - 2.60kg - 5605423803426

**PROFESSIONAL**
**FS267**
**DOUGLAS PRO - ARBORIST HARNESS**


DOUGLAS PRO é um arnês projetado especificamente para arborismo e posicionamento de trabalho. Em conformidade com a EN813 e EN358, este equipamento está equipado com uma ponte flutuante, um recurso fundamental para fazer o movimento lateral em áreas restritas. Possui uma placa de ancoragem para permitir que os utilizadores tenham 3 posições de assento para diferentes necessidades. Tem vários suportes de ferramentas integrados e acessório para suporte de motosserra na parte traseira. O arnês tem fivelas laterais para ajuste em ponte e otimiza o conforto e o posicionamento correto. Tem um acolchoamento especial Croc com sistema de fluxo de ar para maior conforto e trabalho com técnicas de corda estacionária.


**Informação Técnica**

TEMPO DE VIDA ÚTIL	10
CARGA MÁXIMA	CE - 140kg
INSPEÇÃO	Yearly
RASTREABILIDADE	S/N RFID QR Code
NORMAS	CE - EN358:2018 CE - EN813:2008
INTRASTAT	63079098

**Imagens do Produto**


**ESPECIFICAÇÕES**

COMPONENTES METÁLICOS	Aluminium, steel
COMPONENTES TÊXTEIS	Polyester, static rope
OUTROS MATERIAIS	Elastic (webbing keeper)
TIPO DE FITA	PES 30mm with high-abrasion resistance
D-RINGS	ALU d-ring at sides
PONTOS DE ANCORAGEM (A)	2
PADDING LOMBAR	Yes - Croc Extra Hard Padding 3.0
PADDING PERNA	Yes - Semi rigid wide leg pad
PONTO LIGAÇÃO DE CADEIRA	No
SUORTE DE FERRAMENTAS	10 + reinforced point at back for chainsaw
PONTOS DE AJUSTE	7
FIVELAS	3 ALU quick connect buckles; 2 ST bar buckles
INDICADORES DE QUEDA	No
PESO POR TAMANHO   EAN POR TAMANHO	FS267-S/M - 2.40kg - 5605423803655 FS267-XXL - 3.00kg - 5605423803662 FS267-L/XL - 2.60kg - 5605423803426