



PROFESSIONAL

FS243.02

SPINDEL® COMBO 2

SPINDEL® COMBO 2 is a fall protection harness which design allows an optimized upright body position and support for extended working hours at difficult access. The airflow through all the harness layers is assured by the new and improved Croc 3.0 padding which also allows for more comfort without loss of mobility from the user. The Croc innovation allows for lighter and more ergonomic final product and this makes it extremely comfortable for several hours in suspension. COMBO 2 has multiple tool holders points on its belt allowing the user to keep the tools easy to reach. This harness is identified with a RFID tag, S/N label and QR Code for easier traceability and control.



TECHNICAL INFORMATION

LIFESPAN	10
MAXIMUM LOAD	CE - 140kg
INSPECTION	Yearly
TRACEABILITY	S/N RFID QR Code
STANDARDS	CE - EN361:2002 CE - EN358:2018 CE - EN813:2024
INTRASTAT	63079098

PRODUCT PHOTOS



SPECIFICATIONS

METAL PARTS	Aluminium, steel
TEXTILE PARTS	Polyester
OTHER COMPONENTS MATERIAL	PA6, silicone
WEBBING TYPE	PES 45mm water-repellent
D-RINGS	Front, back, ventral and side
ANCHOR POINTS (A)	5
SHOULDER PADDING	Yes - Croc Smooth Padding 3.0
LUMBAR PADDING	Yes - Croc Smooth Padding 3.0
LEG PADDING	Yes
PADDING MATERIAL	TPU, EVA, PA, high visibility mesh and fabric PES
SEAT CONNECTION POINT	Yes
TOOL HOLDERS	5
TOOL HOLDERS MAX LOAD	15kg
ADJUSTMENT POINTS	7
BUCKLES	2 ALU IZY quick connect buckles; 5 ST 3-bar buckles
FALL ARREST INDICATORS	Yes
LANYARD KEEPERS	Yes
COMPONENTS	Safety Technology - FALL SAFE INSPECTOR®
WEIGHT PER SIZE EAN/UPC PER SIZE	FS243.02-S/M - 2.00kg - 5605423820355 FS243.02-XXL - 2.20kg - 5605423751222 FS243.02-L/XL - 2.30kg - 5605423751215 FS243.02-L-022 - 2.30kg - 5605423805550 FS243.02LX-1355 - 2.30kg - 5605423804294 FS243.02-M-022 - 2.10kg - 5605423805543 FS243.02-S-022 - 2.00kg - 5605423805536 FS243.02SM-1355 - 2.00kg - 5605423804287 FS243.02-XL-022 - 2.10kg - FS243.02XX-1355 - 2.20kg - 5605423804270



PROFESSIONAL

FS243.02

SPINDEL® COMBO 2

SPINDEL® COMBO 2 is a fall protection harness which design allows an optimized upright body position and support for extended working hours at difficult access. The airflow through all the harness layers is assured by the new and improved Croc 3.0 padding which also allows for more comfort without loss of mobility from the user. The Croc innovation allows for lighter and more ergonomic final product and this makes it extremely comfortable for several hours in suspension. COMBO 2 has multiple tool holders points on its belt allowing the user to keep the tools easy to reach. This harness is identified with a RFID tag, S/N label and QR Code for easier traceability and control.



INFORMATIONS TECHNIQUES

DURÉE DE VIE	10
CHARGE MAXIMALE	CE - 140kg
INSPECTION	Yearly
TRAÇABILITÉ	S/N RFID QR Code
NORMES	CE - EN361:2002 CE - EN358:2018 CE - EN813:2024
INTRASTAT	63079098

PHOTOS PRODUIT



SPÉCIFICATIONS

WEIGHT PER SIZE EAN/UPC PER SIZE

FS243.02-S/M	- 2.00kg	- 5605423820355
FS243.02-XXL	- 2.20kg	- 5605423751222
FS243.02-L/XL	- 2.30kg	- 5605423751215
FS243.02-L-022	- 2.30kg	- 5605423805550
FS243.02LX-1355	- 2.30kg	- 5605423804294
FS243.02-M-022	- 2.10kg	- 5605423805543
FS243.02-S-022	- 2.00kg	- 5605423805536
FS243.02SM-1355	- 2.00kg	- 5605423804287
FS243.02-XL-022	- 2.10kg	-
FS243.02XX-1355	- 2.20kg	- 5605423804270



PROFESSIONAL

FS243.02

SPINDEL® COMBO 2

SPINDEL® COMBO 2 é um arnês de proteção contra quedas cujo design permite uma posição vertical otimizada do corpo e suporte para longas horas de trabalho em locais de difícil acesso. O fluxo de ar através de todas as camadas do arnês é garantido pelo novo e aprimorado padding Croc 3.0, que também permite mais conforto sem perda de mobilidade do utilizador. A inovação do Croc permite um produto final mais leve e ergonómico e isso torna-o extremamente confortável por várias horas em suspensão. O COMBO 2 possui vários pontos porta-ferramentas no seu cinto, permitindo ao utilizador manter as ferramentas de fácil acesso. Este arnês é identificado com uma etiqueta RFID, etiqueta S/N e QR Code para facilitar a rastreabilidade e o controlo.



Informação Técnica

TEMPO DE VIDA ÚTIL	10
CARGA MÁXIMA	CE - 140kg
INSPEÇÃO	Yearly
RASTREABILIDADE	S/N RFID QR Code
NORMAS	CE - EN361:2002 CE - EN358:2018 CE - EN813:2024
INTRASTAT	63079098

Imagens do Produto



ESPECIFICAÇÕES

COMPONENTES METÁLICOS	Alumínio, aço
COMPONENTES TÊXTEIS	Poliéster
OUTROS MATERIAIS	PA6, silicone
TIPO DE FITA	PES 45mm repelente à água
D-RINGS	Frente, costas, ventral e lateral
PONTOS DE ANCORAGEM (A)	5
PADDING OMBROS	Sim - Croc Smooth Padding 3.0
PADDING LOMBAR	Sim - Croc Smooth Padding 3.0
PADDING PERNA	Sim
MATERIAL DO PADDING	TPU, EVA, PA, malha e tecido alta-visibilidade PES
PONTO LIGAÇÃO DE CADEIRA	Sim
SUPORTE DE FERRAMENTAS	5
CAPACIDADE MÁX. DO SUPORTE DE FERRAMENTAS	15kg
PONTOS DE AJUSTE	7
FIVELAS	2 fivelas de conexão rápida ALU IZY; 5 fivelas ST de 3 barras
INDICADORES DE QUEDA	Sim
SUPORTE DE LONGES	Sim
COMPONENTES	Tecnologia de Segurança - FALL SAFE INSPECTOR®
WEIGHT PER SIZE EAN/UPC PER SIZE	FS243.02-S/M - 2.00kg - 5605423820355 FS243.02-XXL - 2.20kg - 5605423751222 FS243.02-L/XL - 2.30kg - 5605423751215 FS243.02-L-022 - 2.30kg - 5605423805550 FS243.02LX-1355 - 2.30kg - 5605423804294 FS243.02-M-022 - 2.10kg - 5605423805543 FS243.02-S-022 - 2.00kg - 5605423805536 FS243.02SM-1355 - 2.00kg - 5605423804287 FS243.02-XL-022 - 2.10kg - FS243.02XX-1355 - 2.20kg - 5605423804270